

ARCHITECTURE FOR MULTIPLE CHANNEL ACCESS  
TO APPLICATIONS

5

Field of the Invention

The present invention relates to computer systems and, more particularly, to methods and systems for the integration of multiple types of devices for accessing Internet based applications.

10

Background to the Invention

The growth of interest and participation in the Internet has led to a clamor for more ways of accessing Internet based applications. Consumers now use the Internet for tasks which a mere five years ago were considered to be the sole territory of the personal computer. Web based applications now allow people to store, access, modify, and retrieve, among others, their calendars, bank transactions, e-mail, telephone messages, appointments, and contact lists through the Internet. These same consumers now want the ability to access these Internet based applications anywhere using physically smaller devices. Of course, this must be done without compromising the lowest common denominator among most consumers -- the personal computer (PC) based Internet browser. Accordingly, any solution must preserve the Internet application's workstation centric core. However, at the same time these applications should also allow such diverse devices as WAP (Wireless Application Protocol) enabled mobile telephones, palmtop computers, regular telephones, and personal digital assistants (PDAs) to access its functions.

15

20

25

30

35

To answer the above need, a number of solutions have been attempted with mixed results. Web based applications have been customized to run on these smaller devices with the devices accessing them through specific web portals. Such an approach is, unfortunately, quite expensive. Not only is a rewrite of the application required for each and every device type, there is also no guarantee that the rewritten application will have the functions of the original application.

Another attempted solution is the shrinking of web browsers so that they can run on these devices. Unfortunately, the applications, optimized for PCs, are not suitable for such an approach. The small screen (if any) and the limited capabilities of the devices have led to consumer frustration with this approach. Furthermore, the relatively slow speed of the connection between the device and the portal, normally through a wireless modem, also leads to consumer frustration.

Another drawback to such devices is the lack of scripting capability of the browsers of such devices. A further wrinkle to the problem is the need to customize each attempted solution to a specific device platform. A solution which may work properly with a WAP enabled cellular telephone may not work properly with a PDA and vice versa. Also, what may work with a cellular telephone is almost guaranteed not to work with a regular telephone connected to a PSTN (public switched telephone network).

A suitable solution to the above should be flexible, scalable, and must work equally well with any and all devices which are currently being used to access the Internet. Such a solution should also be

transparent to the user and should facilitate rather than hamper a user's access to the Internet application.

5     Summary of the Invention

          The present invention provides systems and methods which allow an Internet based application to be accessed by any device capable of accessing a specific portal without requiring an intensive  
10     rewriting of the application. Indeed, while an API is desirable, no access to the application's source code or application programming interface(API) is required. A three layered system is placed between the application and the accessing device. The first  
15     layer is an AMI (Application Mediation Interface) component directly connected with the application. This application component is able to directly access any data stored by the application. A second layer is a broker layer which mimics the general user  
20     interface logic of the application. The broker layer emulates the UI (User Interface) workflow of the application and, when required, requests data from the application through the application component. The third layer is a DMI (Device Mediation Interface)  
25     component which communicates directly with the end user device. The DMI component receives data from the broker layer and converts this data into user interfaces, data screens, or prompt screens which the end user device can both understand and present to  
30     the end user.

          In a first aspect the present invention provides a system for enabling multiple types of end user devices to access an application, said system comprising:

- 35           - an AMI (Application Mediation Interface)

component communicating with said application;  
- a DMI (Device Mediation Interface) component communicating with said devices; and  
- a broker module communicating with said DMI component and with said AMI component,

5

wherein

- said DMI component converts end data received from said broker module into a format suitable for said devices;

10

- said DMI component transmits replies to prompts from said broker module based on an end user's input into said devices;

- said broker module emulates a sequence of events and decisions followed by said application;

15

- said broker module provides application data functions from said AMI component based on said broker module emulating said application;

- said AMI component receives requests from said broker module and transmits replies to said requests to said broker module based on original data from said application; and

20

- said broker module transmits end data to said DMI component, said end data being based on at least one factor chosen from the group comprising:

25

- said broker module's emulation of said application; and

- application data received from said AMI component.

30

In a second aspect the present invention provides a method of enabling multiple types of end user devices to access an application, said method comprising:

35

- emulating a sequence of events and decisions

followed by said application at a broker module

- requesting application data from an AMI (Application Mediation Interface) component based on an emulation of said application by said broker module, said AMI component communicating with said application;
- transmitting application data requested to said broker module from said application server, said application data being based on original data received from said application by said AMI component, and
- transmitting end data to a DMI (device Mediation Interface) component, said end data being based on at least one factor chosen from the group comprising:
  - said broker module's emulation of said application;
  - application data received from said AMI component;
  - converting said end data at said DMI component into a format suitable for an end user device communicating with said DMI component.

## 25 Brief Description of the Diagrams

A better understanding of the invention may be obtained by reading the detailed description of the invention below, in conjunction with the following drawings, in which:

30 Figure 1 is a block diagram of a system according to the invention;

Figure 2 is a block diagram similar to figure 1 but with multiple broker modules and multiple applications; and

35 Figure 3 is a detailed block diagram of the

system whose implementation is described below.

Detailed Description of the Preferred Embodiment

Referring to Figure 1, a block diagram of a system in accordance with the invention is illustrated. An Internet based application 10 communicates with an AMI (Application Mediation Interface) component 20. Coupled to the AMI component is a broker module 30 which, in turn, is coupled to a DMI (Device Mediation Interface) component 40. The DMI component 40 communicates with an end user device 50. The broker module 30 is unique to each application as it reproduces the workflow or the top level logic of the application 10. However, the AMI component 20 abstracts the data of the application 10 so that, when required, the broker module may request application data from the application 10 through the AMI component 20. This application data is then converted and/or added to by the broker module prior to being passed on to the DMI component 40. The DMI component 40 is equipped to receive this end data and convert such data into a format suitable for whichever end user device is connected to it.

The above scheme does not compromise the Internet capability of the application 10. As can be seen in Fig 2, the invention can accommodate multiple applications, multiple end user devices, and still allow regular personal computers access to the applications. From Fig 2, multiple applications 10A, 10B, 10C, and 10D are communicating with the AMI component 20. For each application, a separate broker module is available. Broker 30A corresponds to application 10A, broker 30B corresponds to application 10B, broker 30C and broker 30D correspond

to applications C and D respectively. Also, multiple devices can be connected to the DMI component.

Device 50A is a palmtop PC, device 50B is a WAP enabled cellular phone, device 50C is a telephone  
5 connected to a PSTN, and device 50D is a PDA. The Internet 60 also connects a regular PC 70 with the applications 10A-10D.

It should be noted that each of the end user devices 50A-50D communicate differently with the  
10 DMI component and each one requires a different data format. The palmtop PC can be connected by means of a regular modem while the PDA can be connected by a wireless modem. The WAP cellphone can be connected by its wireless link to the service provider while  
15 the telephone 50C is connected by a regular telephone line and a suitable interface.

In a specific implementation, the broker module functions are accomplished by the use of a script written in an XML (extended markup language) derived markup language MCML (multi-channel mark up  
20 language). Each script follows and details the workflow of the application for which it is written. When required, the script, through a machine running it, calls for data from the AMI component. The  
25 script is device independent and AMI component independent. However, as noted above, it details the workflow or top level logic (events and decisions) of the application. Thus, the script will have the user prompts, the choices associated with such prompts,  
30 user input fields, data delivery, and the flow decisions associated with such options. The script, will, however, not mimic the deep functions of the application. It is simply a data delivery mechanism -- it prompts, receives, and delivers data to the end  
35 user through the DMI component. To do this, it

requests and receives data from the AMI component. It then reformats and/or adds to the data before sending it on to the DMI component.

5       The AMI component is a stateless module in that it does not store nor even care about what state or step the application is in. What the AMI component does is to receive the broker module's requests and fulfills those requests by interfacing with the application.

10       The DMI component is essentially a converter -- it receives data from the broker module and converts that data into a format suitable for whatever device is requesting it. Thus, if the end user device is a telephone 50C, then the DMI  
15       component converts the data into a Voice XML document and funnels it to a text-to-speech converter so that the data may be read to end user. Conversely, if the device is a WAP enabled cellphone, the data is converted into a WML (WAP markup language) document  
20       and transmitted to the end user cellphone. Thus, the data is now in a format which can be read and understood by the end user device. Similarly, if the data sent to the end user requires an input from an end user, the document produced by the end user  
25       device is converted to a format suitable for the broker module. Thus, if the device is the PSTN phone 50C in Fig 2, the end user either speaks the required input or enters it through the keypad. If spoken, the end user's voice is converted, through a voice  
30       recognition system in the DMI component, into a Voice XML document. This is then converted into a format recognizable by the broker module.

      To manage security and user authentication, an authentication manager is deployed in the system.  
35       Such an authentication manager receives the user's



credentials such as, name, password and authenticates them. Once authenticated, a session manager, implemented within the broker module, manages that user's transactions. The session manager can serve a twofold duty -- not only does it keep track of the user's actions but it would store the state that an application is in. Since the AMI component is stateless and since most applications are state driven, the session manager will store and monitor the application's state. Because of this, it is simpler for the AMI component to retrieve data from the application. As an example, if data A can only be accessed in the application by passing through states A1, A2, and A3, then an AMI component, not having any states, would be hard pressed to find such data. The AMI component may, in a single session, have to always go through those states just to keep accessing the data A. However, if the application is already in state A3 and the session manager has saved this state and has kept the application in this state, then any other time the AMI component requests data A, it would be ready.

To further clarify, the broker module block uses the MCML language in which an MCML flow describes a set of states, to be interpreted by a finite state machine (FSM). These states represent device-independent "forms" which may contain "widgets". The DMI component or Device Adaptor (DA) implicitly implements the FSM and dynamically translates these states to the target devices' markup language.

The syntax blocks representing states, stored in one or more MCML documents, are implemented using XML, and can thus be validated. An application workflow consists of one or more linked MCML

documents.

There are different types of MCML blocks.

These can be :

- Text processing block
- Menu processing block
- GetInput processing block
- UserDefined processing block

Blocks can contain tags that may not be used by all devices. It is up to the translating process to select the tags appropriate to the target device. This allows the application flow writer to fine-tune application behaviour to suit devices with special capabilities. For example, some tags control telephony features which are not useful for HTML devices, but which may be useful for a Voice XML device. In that sense, some tags may be redundant in MCML, and would be filtered to produce the device-targeted documents.

MCML documents can be produced or generated using any text editor. It is suggested that a validating editor or parser be used however, to ensure correctness. Alternately, the Saxon XML parser (or any other compliant XML parser) can be used to validate the MCML based on the DTD.

Each application enabled by the multi-channel system requires an MCML flow, which can be implemented as one or more MCML documents. These documents should reside in a dedicated directory to avoid the risk of name clashes with other applications' MCML files. For example, for an expense reporting application, the MCML files may be called:

```
.../ExpenseReporting/main.mcml
.../ExpenseReporting/dataEntry.mcml
.../ExpenseReporting/dataRetrieval.mcml
```

The application's flow is abstracted into a

series of linked states, represented by MCML blocks within MCML documents. States consist of generic widgets, as detailed below. These are translated into the target device-specific widgets by the device adaptor, once all dynamic content, if any, has been inserted by embedded Java method calls.

Placeholders for EJB (Enterprise Java Beans used to implement a portion of the AMI component or application adaptor) and local class calls can represent dynamic content. Special tags specify the method name and parameters required. The local or remote classes are then called through a filter/macro-processor class that returns an MCML block (a string). This block replaces the placeholder tag, and processing continues, with the eventual XSLT translation of the entire MCML document into the target mark-up language page, which is then forwarded to the client.

In one implementation, the following guidelines, standards and subsystems were used :

1. J2EE standard (Sun Microsystems) compliant application server.
2. SAXON 5.4.1 XSLT/XML processor.
3. Web Logic Server 5.1 provides the application server and container framework for all classes. The Commerce Server provides the Web-based Personal Interaction Centre (PIC is MASP's (Managed Application Services Platform) name for a portal) features upon which the multi-channel PIC (not described in this document) is based.
4. Each application's UI flow must be described by a specific set of MCML documents.
5. An XSL style sheet per channel type

(VoiceXML, WML, HDML, etc) is required to translate the MCML to the target mark-up language.

6. A Device Adaptor (DA) servlet is used to dynamically generate Voice XML/WML/HTML or other pages using SAXON XSLT to translate the MCML document/script.

7. Error handling is done through Java's remote exception mechanism. AMI Components throw exceptions that are caught and processed by the DA.

Ideally, the following conditions are to be applied in implementing the system:

1. All EJB's and classes that generate dynamic content within the MCML flows must be stateless session beans that are written to conform to the EJB documentation for multi-channel access.

2. Every request from devices must carry a session ID within URL and the current block name.

3. Caching may be done by the DA to avoid latency in reloading and translating MCML. Default application flow behaviour and

default block parameters can be set in a special MCML block.

The following (global) properties can be set:

1. Timeout in seconds for user input response.

2. Number of prompt repetitions before failure.

### 3. Global URL prefix.

4. Name of starting block.

5. Name of default error processing block.

6. Name of exit/abort block.
7. Session timeout.

Example:

```
<!--(default settings)-->
5   <globalproperties>
      <property name="timeout" type="int" value="30"/>
      <property name="repeatnum" type="int"
value="3"/>
      <property name="systemURL" type="text"
10  value="www.nortelnetworks.com"/>
      </globalproperties>
```

MCML states can be categorized into the following types of blocks:

- Text display;
- 15 • Menu options;
- Get user input;
- User-defined (method call).

A complete MCML application flow must also include other descriptions, such as error handling, version definitions, and embedded comments. These can be categorized as follows:

- Global properties;
- Error handling block;
- Version description;
- 25 • Copyright description;
- Default settings - it includes timeout and other configuration information;
- Disconnect block - to handle hang-up events during telephony access.

30 MCML inherits its syntactic constructs from XML. Reference to XML specification should be made for in-depth information on syntactic issues. The MCML is defined in Backus-Naur Form (BNF which is a generic meta-language used to describe computer language) format as follows:

35

```

ApplicationFlow ::= <?xml version= "1.0"?>
<mcml>
    <applicationname/>application name
5    <copyright>copyright description</copyright>
    <version>version description</version>
    (default settings)
    <globalproperties>(properties)</globalproperties>
    <errorhandle>(processing block
10 name)</errorhandle>
    <startblock>(processing block name)</startblock>
    <endblock>(processing block name)</endblock>
    (FSMflow)
</mcml>
15 deaefaultsettings ::=
<defaultsettings>
    <timeout/> timeout
    ...
</defaultsettings>
20 properties ::= <properties>(property)?</properties>
property ::=
<property>
    <name/>property name
    <type/> (int | long | double | float | string |
25 date | time)
    <size/> size of the property
    <value/> value of the property
    <default/>default value
</property>
30 default definitions ::=
    <default>
        (properties)
    </default>
    FSMflow ::=
35 <FSMFlow>

```

```

        (processing block)*
    </FSMFlow>

```

```

Processing block ::=

```

```

5      TextBlock | MenuBlock | GetInputBlock |
      UserDefinedBlock

```

```

blockbody ::=

```

```

      (Text block | Menu block | GetInput block | List
      block | UserDefined block)

```

```

10      MCML text processing blocks allow the
      display of text. This content can be either
      dynamically generated by an EJB or class, or can be
      static. Text blocks can also define buttons, for use
      with WAP browsers. These are not used in Voice XML.

```

```

15      The grammar is as follows:

```

```

Text block ::=

```

```

<block blocktype="TextBlock" blockname="blockname">

```

```

    [(action)]

```

```

    <properties>(property)?</properties>

```

```

20    <prompt>(Message)?</prompt>

```

```

    <buttonsettings>(buttonsetting)*</buttonsettings>

```

```

    // for WAP

```

```

    (<text>(text content)</text>)*

```

```

    <nextblocks>

```

```

25    (<hitbutton name="buttonname"

```

```

    goto="nextblockname"/>)*

```

```

    </nextblocks>

```

```

    </block>

```

```

action ::=

```

```

30    <action>

```

```

        <method name="methodname" [type="ejb"]

```

```

        interface="interfacename" [jndi="jndi-path"]>

```

```

        <params>

```

```

            (<param name="param-name" type="text"/>)*

```

```

35    </params>

```

0000013499ROUS01U

```

        <result name="result"/>
        </method>
    </action>
    text content :: = [$(property name) | user-defined
5    text]

```

MCML menu blocks generate a list of choices on the device. When the user selects one, the FSM will go to the associated next state. Menu choices can cause variables to be set. These variables are typically used to maintain state and are managed by the DA/FSM. These are saved using the state manager to allow multiple simultaneous sessions. The menu items may be static or dynamically generated by embedded method calls.

The XML description of this processing block is as follows:

Menu block ::=

```

<block blocktype="MenuBlock" blockname="blockname">
20    <properties>(property)?</properties>
        // not currently used
    <prompt>(Message)?</prompt>
        // menu title string
    <menuitems>
25    (<menu title="your menu name" id="your menu
id"/>)? //the items
    </menuitems>
    <choices>
        (<nextblock id="your menu id"
30    goto="nextblockname" dtmf="digits"/>
        )? // nextblock definitions must match
    menuitems
    </choices>
    </block>

```



The MCML GetInput processing block is used to collect the input data from a user. It posts an input form page on the device's browser first and then waits for the input.

5 The syntax description is as follows:

GetInput block ::=

<block blocktype="GetInputBlock"

blockname="blockname">

<properties>

10 (property)?

</properties>

<prompt>(Message)?</prompt>

<buttonsettings>(buttonsetting)\*</buttonsettings>

// for WAP

15 <form title="form title">

(formitem)?

</form>

<nextblocks>

<filled>block name</filled>

20 <timeout>hangup block</timeout>

<defaultblock>block name</defaultblock> //

handle default case

</nextblocks>

formitem ::=

25 <input name="fieldname"

type=(password | text | numeric)

size=the length of the field

title="fieldname">

default= the default value for this field

30 </input>

The UserDefined MCML processing block is a data processing block. It does not post any page to the browser at all. It serves to make method calls to the application adaptor EJB methods, or optionally to local classes. The resulting output is saved in

35

FSM variables and can be used in subsequent processing blocks. The syntax description is as follows:

UserDefinedblock ::=

```

5  <block blocktype="UserDefinedBlock"
    blockname="blockname">
        <properties>
            (property)?
        </properties>
10  [action]
        <nextblocks>
            <failure>block name</failure>
            <success>block name</success>
            <defaultblock>block name</defaultblock>    //
15  handle default case
        </nextblocks>
    </block>

```

#### Integration Details

20 For each application, an MCML flow must be written to describe the application workflow. The associated EJB's and called classes must also be written, and the linkage between the MCML variable name, state names, and class names must be done so

25 that these can work in concert. This means that the EJB's and MCML must be written with a knowledge of each other.

To test, the EJB's must be deployed on the application server, the MCML files stored under the public\_html directory hierarchy, and the DA invoked using a client.

30

The appropriate XSL style sheet can be passed as a request parameter to the DA, and the resulting target specific mark-up should be returned.

35

Return Codes and Error Handling

EJB's or other called classes return errors using one of two mechanisms:

1. Throwing a remote exception, to be caught by the DA.

2. Returning a null string instead of dynamically generated MCML.

Both are handled in the same way:

The DA will detect the error;

- if the method called was not part of an EJB, or if it was not an authentication exception, or if the retries above failed, then the DA will go to the failure branch in the UserDefined block that called the method. This should point to a block that handles the error, either by notifying the user, or attempting retries;

- the DA reserves a special variable called `_error` Message that is guaranteed to always contain the string returned by the last exception caught.

Example Usage

Two examples of MCML code follow:

```
<?xml version= "1.0"?>
```

```
<!-- filename:  calendar.mcml -->
```

```
<!-- Date:  August 22, 2000 -->
```

```
<!-- The following MCML document describes a Calendar application workflow.
```

note: It assumes authentication is passed.

The description of workflow is as follows:

1. Calendar application welcome page  
(Text)

C: Welcome to the Calendar application.

```

    goto 2 ask for date
2. Ask for the appointment date
(GetInput)
    C: Please say the appointment date.
5    goto 3 get summaries
    3. Get the summaries of the specified
date (UserDefined)
    Call EJB to get summaries for the
specified day
10    save summaries in somewhere else.
    got 4 play summaries.
    4. Say the summaries (Menu)
        repeat        goto 4
        detail        goto 5 ask for the
15                    specified time
    other day        goto 2 ask for date
    5. Ask for time (GetInput)
        goto 6 to get the detail
    6. Get the detail (UserDefined)
20    Call EJBs to get the detail and save it
somewhere else.
        goto 7 to play the detail.

    7. Play the detail (Menu)
25    repeat        goto 7
        other appointment goto 5 ask for time
        other day        goto 2 ask for date
-->
<mcml>
30    <applicationname>Calendar</applicationname>
    <copyright>Nortel Networks Copyright. July,
2000</copyright>
    <version>MCML Version 1.0</version>
    <!--(default. settings)-->
35    <globalproperties>
```

```

1      <property name="timeout" type="int"
value="30"/>
      <property name="repeatnum" type="int"
value="3"/>
5      <property name="systemURL" type="text"
value="www.nortelnetworks.com"/>
      <property name="userid" type="text"/>
      <property name="password"
type="password"/>
10     </globalproperties>
      <errorhandle>
          <hangup blockname="hangupblock"/>
          <error blockname="errorblock"/>
      </errorhandle>
15     <FSMFlow>
          <block blocktype="TextBlock"
blockname="start">
              <!-- ask for date -->
              <text> Welcome to the Calendar
20     application. </text>
              <nextblocks defaultblock="askfordate">
                  <timeout goto="disconnect"/>
              </nextblocks>
          </block>
25     <block blocktype="GetInputBlock"
blockname="askfordate">
              <!-- ask for date -->
              <prompt>
                  <message msgmode="Voice XML"
30     msgtype="text" content="Please say the appointment
date."/>
              </prompt>
              <form>
                  <input name="date" type="date"
35     title="date"/>

```

```

        </form>
        <nextblocks defaultblock="getsummaries">
            <!-- demo .. goto hangup -->
            <filled goto="getsummaries">
5              <output name="date" type="date"/>
            </filled>
        </nextblocks>
    </block>
    <!-- need a specific implementation using
10   servlet or java class -->
        <block blocktype="UserDefinedBlock"
            blockname="getsummaries">
            <properties/>
            <action>
15                <!--method name="getSummaries"
                    interface="com.nortel.masp.mca.MCML.CalendarWrapper"
                    source="http://localhost:7001"-->
                    <!--method name="makeEJBcall"
                        interface="com.nortel.masp.mca.MCML.CalendarWrapper"
20                     source="http://localhost:7001"-->
                        <!--method name="getSummaries"
                            type="ejb"
                            interface="com.nortel.masp.mca.MyCalendarRemote"
                            ejbhome="com.nortel.masp.mca.MyCalendarHome"
25                         jndi="mca.MyCalendarHome"
                            ejbhost="t3://localhost:7001"-->
                                <method name="getSummaries" type="ejb"
                                    interface="com.nortel.masp.mca.MyCalendarRemote"
                                    jndi="mca.MyCalendarHome">
30                                <params>
                                    <!--param
                                        name="remote=com.nortel.masp.mca.CalendarRemote"
                                        type="text"/-->
                                    <!--param
35                                name="jndi=mca.CalendarHome" type="text"/ -->

```

```

    <param
name="CalendarURL=http://wleey006.ca.nortel.com"
type="text"/>
    <param name="port=81" type="text"/>
    <param name="username=demo"
type="text"/>
    <param name="password=new2day"
type="text"/>
    <param name="date" type="text"/>
  </params>
  <result name="summariesmenu"/>
</method>
</action>
<nextblocks>
  <success goto="saysummaries"/>
  <failure goto="noappointment"/>
</nextblocks>
</block>
<block blocktype="MenuBlock"
blockname="saysummaries">
  {$summariesmenu}
</block>
<block blocktype="TextBlock"
blockname="noappointment">
  <properties/>
  <prompt/>
  <buttonsettings>
    <button buttontype="accept"
label="back"/>
    <button/>
  </buttonsettings>
  <text>No appointment for this day</text>
  <nextblocks defaultblock="askfordate">
    <hitbutton name="back"
goto="askfordate"/>
  </nextblocks>
</block>
</page>

```

```

        </nextblocks>
    </block>
    <!-- it needs a specific servlet or class
to implement this block -->
5      <block blocktype="UserDefinedBlock"
      blockname="getdetail">
        <properties/>
        <action>
          <method name="getDetail" type="ejb"
10      interface="com.nortel.masp.mca.MyCalendarRemote"
      jndi="mca.MyCalendarHome">
            <params>
              <param name="UID" type="text"/>
              <param name="port=81" type="text"/>
15      <param name="username=demo"
      type="text"/>
              <param name="password=new2day"
      type="text"/>
            </params>
20      <result name="detail"/>
          </method>
        </action>
        <output><property name="detail"
      type="text"/></output>
25      <nextblocks>
          <success goto="saydetail"/>
          <failure goto="saynoappointment"/>
        </nextblocks>
      </block>
30      <block blocktype="MenuBlock"
      blockname="saydetail">
        <properties/>
        <prompt>
          <message msgtype="text" content="your
35      appointment is as follows: "/>

```



```
<message msgtype="text"
content="{ $detail }"/>
    <message msgmode="Voice XML"
msgtype="text" content=" Please choose one of the
5 following options: summary, another day, or
repeat."/>
        </prompt>
        <menuitems>
            <menu title="repeat" id="repeat"/>
10        <menu title="back to summary"
id="summary"/>
            <menu title="another day" id="another
day"/>
        </menuitems>
15        <choices defaultblock="askfortime">
            <nextblock id="repeat"
goto="saydetail"/>
            <nextblock id="summary"
goto="saysummaries"/>
20        <nextblock id="another day"
goto="askfordate"/>
        </choices>
    </block>
    <block blocktype="TextBlock"
25 blockname="saynoappointment">
        <!-- ask for date -->
        <action>
            <method name="toSpeakableDate"
interface="com.nortel.masp.mca.MCML.MCMLutils">
30        <params>
            <param name="date" type="text"/>
        </params>
            <result name="speakableDate"/>
        </method>
35    </action>
```

```
<prompt>
    <message msgtype="text" content="No
5  appointment on {$speakableDate}"/>
    </prompt>
    <nextblocks defaultblock="askfortime">
        <timeout goto="hangup"/>
    </nextblocks>
    </block>
10  <block blocktype="TextBlock"
    blockname="hangup">
        <buttonsettings>
            <button buttontype="accept"
15  label="OK"/>
            <button/>
        </buttonsettings>
        <text>Thank you for calling calendar
        application. Goodbye.</text>
        <nextblocks defaultblock="disconnect">
20  <hitbutton name="OK"
        goto="askfordate"/>
        </nextblocks>
    </block>
    <block blocktype="DisconnectBlock"
25  blockname="disconnect">
        <disconnect/>
    </block>
    </FSMFlow>
    </mcml>
```

```
<?xml version= "1.0"?>
<!-- filename:  IMAP4.mcml -->
<!-- Author:    T. Barake -->
5 <!-- Date:     Sept 12, 2000 -->
  <!-- The following MCML document describes a
  Messenger application workflow.
```

note: It assumes authentication has occurred and stored in session manager

10 Workflow states:

MAIN

Email main menu

```
1- Get list of unread mail headers
```

goto UNREAD

```
15          2- Choose a mailbox          - goto
```

SETBOX

3- Contact list - goto

## CONTACTS

20 EXITtoIMAP

UNREAD

```
Menu of unread headers if any
otherwise
```

Display a message saying no unread

25 messages

uses:

SELECT MAIN

SELECT

Display the detail

30 uses:

UNREAD MAIN

SETBOX

Menu of available mailboxes is displayed

```
35          SELECTBOX      MAIN
```

SELECTBOX

Menu of unread headers if any  
otherwise

```
5      Display a message saying no messages
      uses:
```

DETAIL	MAIN
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

## DETAIL

```

10         Display the detail
        uses:

```

SELECTBOX MAIN

## CONTACTS

Menu of contact headers if any  
otherwise

```
15         Display a message saying no contacts
           uses:
```

SELECTCONTACT MAIN

SELECTCONTACT

```

20         Display the detail on a contact
        uses:

```

CONTACTS                      MAIN

— — — — —

<mcm1>

```

25      <applicationname>Calendar</applicationname>
      <copyright>Nortel Networks Copyright. October,
      2000</copyright>

```

<author>A. Barake</author>

```
<version>MCML Version 1.0</version>
```

```
<!--(default settings)-->
```

&lt;globalproperties&gt;

```
<property name="timeout" type="int" value="30"/>
```

```
<property name="repeatnum" type="int"
value="3"/>
```

```
35      <property name="systemURL" type="text"
```

```
value="www.nortelnetworks.com"/>
    <property name="userid" type="text"/>
    <property name="password"
5    type="password"/>
    </globalproperties>
    <errorhandle>
        <hangup blockname="hangupblock"/>
        <error blockname="errorblock"/>
    </errorhandle>
10    <FSMFlow>
        <block blocktype="MenuBlock"
            blockname="start">
            <properties/>
            <prompt>
15            <message msgtype="text"
                content="Messenger eMail"/>
            </prompt>
            <menuitems>
                <menu title="1. Get unread mail headers"
20                id="1" />
                <menu title="2. Choose a mailbox" id="2"
/>
                <menu title="3. Contact list" id="3" />
            </menuitems>
25            <choices defaultblock="get" dtmf="true">
                <nextblock id="1"
                    goto="FETCHUNREADHEADERS"/>
                <nextblock id="2" goto="SETBOX"/>
                <nextblock id="3" goto="CONTACTS"/>
30            </choices>

            <!-- button required EXITtoIMAP -->
            </block>

35    <block blocktype="UserDefinedBlock"
```

```

        blockname="FETCHUNREADHEADERS">
        <properties/>
        <action>
            <method name="getUnreadMessageHeaders"
5      type="ejb"
        interface="com.nortel.masp.mca.Imap4Remote"
        jndi="mca.Imap4Home">
            <params>
                <param name="mailbox=inbox"
10     type="text"/> <!-- (java.lang.String mailbox) -->
            </params>
            <result name="unreadheadersmenu"/>
            </method>
        </action>
15     <nextblocks>
            <success goto="DISPUNREADHEADERS"/>
            <failure goto="NOMESSAGES"/>
        </nextblocks>
    </block>
20     <block blocktype="MenuBlock"
        blockname="DISPUNREADHEADERS">
            {$unreadheadersmenu}
            <nextblocks defaultblock="MAIN">
                <hitbutton name="OK"
25     goto="DISPDETAILS"/>
                <hitbutton name="back" goto="MAIN"/>
            </nextblocks>
        </block>
        <block blocktype="TextBlock"
30     blockname="NOMESSAGES">
            <properties/>
            <prompt/>
            <buttonsettings>
                <button buttontype="accept"
35     label="back"/>

```

SECRET 2144200

```

    <button/>
  </buttonsettings>
  <text>No unread messages found</text>
  <nextblocks defaultblock="MAIN">
5    <hitbutton name="back" goto="MAIN"/>
  </nextblocks>
</block>
<block blocktype="UserDefinedBlock"
  blockname="SETBOX">
10  <properties/>
  <action>
    <method name="getFolderNames" type="ejb"
      interface="com.nortel.masp.mca.Imap4Remote"
      jndi="mca.Imap4Home">
15    <result name="foldernamesmenu"/>
    </method>
  </action>
  <nextblocks>
    <success goto="DISPFOLDERS"/>
20    <failure goto="NOFOLDERS"/>
  </nextblocks>
</block>
<block blocktype="MenuBlock"
  blockname="DISPFOLDERS">
25    <!-- selecting a folder here
      sends you to the header list fetch for that folder --
    >

    <!-- must return variable called
      foldername with correct folder in it -->
30    {$foldernamesmenu}
    <nextblocks defaultblock="MAIN">
      <hitbutton name="OK"
        goto="FETCHHEADERS"/>
      <hitbutton name="back" goto="MAIN"/>
35    </nextblocks>
```

```

    </block>
    <block blocktype="UserDefinedBlock"
      blockname="FETCHHEADERS">
      <properties/>
5      <action>
        <method name="getAllMessageHeaders"
type="ejb"
interface="com.nortel.masp.mca.Imap4Remote"
jndi="mca.Imap4Home">
10      <params>
        <param name="{ $mailbox}"
type="text"/> <!-- (java.lang.String mailbox) -->
        </params>
        <result name="allheadersmenu"/>
15      </method>
      </action>
      <nextblocks>
        <success goto="DISPHEADERS"/>
        <failure goto="NOMESSAGES"/>
20      </nextblocks>
    </block>
    <block blocktype="MenuBlock"
      blockname="DISPHEADERS">
        <!-- selecting a folder here
25 sends you to the header list fetch for that folder --
>
        <!-- must return variable called
foldername with correct folder in it -->
        { $allheadersmenu }
30      <nextblocks defaultblock="MAIN">
        <hitbutton name="OK"
goto="DISPDETAILS"/>
        <hitbutton name="back" goto="MAIN"/>
        </nextblocks>
35      </block>

```



```

<block blocktype="UserDefinedBlock"
      blockname="DISPDETAILS">
  <properties/>
  <action>
    <method name="getSelectedMessage"
      type="ejb"
      interface="com.nortel.masp.mca.Imap4Remote"
      jndi="mca.Imap4Home">
      <params>
        <param name="{ $mailbox}"
          type="text"/> <!-- (java.lang.String mailbox, int
          mail_Id)-->
        <param name="{ $mail_Id}"
          type="int"/>
      </params>
      <result name="messagedetails"/>
    </method>
  </action>
  <nextblocks>
    <success goto="SHOWDETAILS"/>
    <failure goto="NOMESSAGES"/>
  </nextblocks>
</block>
<block blocktype="TextBlock"
      blockname="SHOWDETAILS">
  { $messagedetails }
  <nextblocks defaultblock="MAIN">
    <hitbutton name="OK" goto="MAIN"/>
  </nextblocks>
</block>
<block blocktype="TextBlock"
      blockname="done">
  <buttonsettings>
    <button buttontype="accept"
      label="OK"/>
  </buttonsettings>
</block>

```

```

        <button/>
    </buttonsettings>
    <text>Thank you for calling the Messenger
application. Goodbye.</text>
5    <nextblocks defaultblock="disconnect">
        <hitbutton name="OK"
goto="askfordate"/>
        </nextblocks>
    </block>
10    <block blocktype="DisconnectBlock"
blockname="disconnect">
        <disconnect/>
    </block>
    </FSMFlow>
15 </mcml>

```

Regarding the authentication manager, the authentication subsystem consists of the front-line authentication servlet, an LDAP directory shared with MASP, and application-specific authentication methods, implemented as part of the application

20 adaptors' EJB. As noted above, the term application adaptor is interchangeably used to refer to the AMI component.

The role of the authentication servlet is

25 to assign a session to the new user, and to maintain and manage this session for authenticated users in conjunction with the Device Adaptor (DA). It assigns a temporary session key during login and a session key after validation, and dispatches the request to the

30 DA. The dispatched request is modified to suit the client browser's protocol and mark-up language, so that the DA can reply appropriately.

A valid login will result in a session key being assigned and the storing of the user's

35 login and password information in the session

5

10

15

20

25

35

negotiation in response to the authentication exception. Such methods are potentially re-usable by multiple EJB's that access similar back-end protocols (for example IMAP4).

5           The following example only covers authentication examples for the following protocols: HTTP, IMAP, LDAP. Further authentication code will have to be written along the same lines to enable single sign-on capability in applications that use  
10 protocols other than these.

          The system is accessed through a single URL, which points to the authentication servlet. This servlet is responsible for dispatching the request in a manner appropriate for the requesting client  
15 browser (ex: WML, HTML, HDML, Voice XML).

          Ideally, the system would use the following requirements :

- Each application adaptor EJB requires a special authentication method called  
20 "login";
- Application adaptor EJB methods must assume that the client connection to the application is stored in the session manager using a special name; and
- 25 - The special name for the authentication exception substring must be defined in the "util.constants" object.

          Normal communications between the application adaptor EJBs and their applications need  
30 an authenticated session. Whether or not this session has been initiated will be checked transparently (as the EJB tries to read the application client from the Session Manager). If the client session cannot be found in the session  
35 manager, an exception will be thrown, which will

prompt the device adaptor to call the special login EJB method to set up this session.

The following design guidelines and tools may be used:

5

1. Java (Sun's JDK 1.2.2) is used for authentication EJB coding.

2. The J2EE 2.0 specification for EJB interface and deployment is adhered to.

10

3. The application adaptor EJB's are stateless, in that any device-side method call can be made at any time. State is maintained outside the EJB's, in the unique Session Manager. Therefore EJB's can be replicated and clustered.

15

4. Getting an authenticated session open to an application must be transparent and be able to re-login to the application if the previous application session has timed out.

20

5. We want to keep the authentication mechanism in the application adaptor EJB as simple as possible.

25

6. Authentication credentials and session dispatching occurs transparently to the DA and application adaptors, and is handled by the exposed authentication servlet.

Ideally, the following conditions will also

apply:

30

1. All EJB's must use the session manager to store state or instance information. No instance variables are allowed. The EJB's should be clusterable across different servers and operate with a single logical session manager.

35

2. Since the client objects stored in the

Session Manager may contain socket handles or files handles (and those handles are not transferable between machines), the device adaptor must always make calls to EJBs on one server only.

Each application adaptor EJB will have a standard method call named "login" which will be used by the device adaptor to set up an authenticated session with the application. This method will take the standard parameters for all application adaptor EJBs: A session manager, and a property list which potentially contains additional parameters (if required).

That session will be read back from the session manager by each EJB method and used to communicate with the application. If the session is created successfully by the login method, it stores it in the session manager using a key name with the following format:

<application name><loginClientSubstring>

The "loginClientSubstring" is retrieved from the util.constants class.

This allows the other EJB methods to retrieve the client connection with the application using a standardized name, and also allows the DA to identify the exception that may be thrown if this key does not exist (no login has yet occurred). The DA does this by parsing for the substring on all received exceptions, and it treats this particular exception as a special case.

The following is a description of the steps taken by the authentication servlet when handling a request:

- If incoming http request contains a system authentication key, check the key (see method below).

If valid, pass the request on to the DA.

- If there is no key associated with the request, or if the key is invalid (it may have expired or may be an attack), challenge the user agent (client browser) as follows:

- Save the incoming URL based on the generated key;
- Generate a temporary key for this reply and forward with device-specific form to the user;
- Call the dispatch method (see key generation description below), to generate a device-specific login form by sending a request to the DA to translate login.mcml;
- The dispatch method determines the type of client (WML, Voice XML, HDML, or HTML). The default type is HTML (settable);
- Record the WebLogicSession key returned from the DA;
- Wait for reply. When received, check the validity of the temp key (see algorithm below);
- Convert user id and password from numeric if required (for Voice XML)
- Lookup the user id/password in the LDAP
- If authentication succeeds, proceed below, otherwise, retry above
- Restore the original URL
- Delete temporary login key
- Create a authentication session key (see key generation description below) and append to request
- Replace authentication key with

```
WebLogicSession key returned from the
login step
```

- Add the userid and password to the request sent to the DA
- Forward the request to the DA

Two types of keys are possible -- temporary and session key with the same contents otherwise.

The steps in the key generation process may be as follows :

- Encode an expiry date (set to 1 hour for session keys, shorter for temp keys, but configurable)
- Encode a random number
- Encode sender's IP (IPV4 or IPV6)
- RSA sign a buffer containing the above 4 items.
- Add the signature to the end of the key buffer
- Base64 encode the buffer

To validate the key, the process may take the following steps :

- decode the key using Base64 decoding
- Split the result into key and signature
- Verify the key using the RSA signature.
- Check key's age - if near expiry (within 10 minutes) and it is a session key, reset the expiry to another hour since this request counts as activity
- Check that the sender's IP still matches that of the sender when the key was created.
- Base further processing on the key type

EJB login methods are required to connect to the back-end applications. The following is a template for such methods.

```
EJB_wrapper (...) {
    try {
        AppEJB.method( SessMgr, parameter1,
parameter2...);
    }
```



```
    }  
    catch InvalidXXX {  
        AppEJB.login( SessMgr );  
    }  
5    }  
    AppEJB {  
        public method1( SessMgr, ... ) {  
            client = SessMgr.getCurrentState().get(  
                "AppCLIENT" );  
10            ...  
        }  
        public method2( SessMgr, ... ) {  
            client = SessMgr.getCurrentState().get(  
                "AppCLIENT" );  
15            ...  
        }  
        public login( SessMgr ) {  
            AuthEJB.login( SessMgr, "AppCLIENT" );  
        }  
20    }  
    AuthEJB {  
        public login( SessMgr, String app ) {  
            // Get userid/password  
            String userid =  
25            sessMgr.getCurrentState().get("userid");  
            String passwd =  
            sessMgr.getCurrentState().get("password");  
            // Connect to LDAP DB with userid/password (if  
            necessary)  
30            // Lookup login credentials for user to login to  
            app  
            // Login to app  
            ClientClass client = new ClientClass(userid,  
            password);  
35            // Store client in sessMgr
```

```
SessMgr.getCurrentState().put( app, client
);
    }
}
```

5                   Concerning the session manager, the multi-channel architecture requires a session manager to maintain user and application session state and to provide dynamic state storage and retrieval services to the application adaptors. Since the application  
10 adaptors may be distributed over several servers, this service must be unique or replica-aware, and must serve all adaptors from the same central session repository. It may of course be implemented as distributed objects drawing from the same database.  
15 The actual mechanism and location of the session repository is transparent to application programmers (device adaptors and EJBs.) The session manager object is passed by reference to all adaptors and EJBs. The session manager implicitly maintains a  
20 session ID. The session ID is embedded in the URL of all transactions with the client, since cookie support cannot be assumed.

The session manager provides the following advantages :

25                   1. Provides user authentication into the application. The application adaptors can use the session manager to access applications.

                  2. Dynamic session instance management that includes application specific instance fields  
30 (containers), for example "session-id" or "phoneNumber". The session manager is used to store such dynamic session state information on behalf of the application and device adaptors.

                  3. User profile management. The multi-  
35 channel session manager maintains the end-user

specific configuration (profile) which includes a list of provisioned applications with associated devices supported (properties). Profiles are created and populated via the Management Interaction Center (MIC) and Business Interaction Center (BIC) interface in the completed system. MIC is a portal for the hosted application provider (HSP) to provision businesses to use MASP applications. BIC is the hosted business portal, used to manage their employees' access to hosted applications. The information is stored using Web Logic's Personalization Server facilities, but would be manually populated for the interim release checkpoints, and for testing purposes. Web-based provisioning is assumed to be as provided by MASP 1.1. Examples of configuration fields on a per-user basis would consist of:

- a) Predefined (by user) e-mail responses
- b) Predefined (by user) appointment summaries and locations
- c) List of enabled applications, and URI's on a per-channel basis
- d) APM related configuration information
- e) PIC preferences
- f) Application specific generic workflows (MCML) for multi-channel enabled applications, and for the PIC.
- g) Application specific time-out overrides.
- h) Sign-on enabling information (APM codes).
- i) User preferences (for the PIC) such as application menu order, internationalization settings, ASR/TTS engine preferences.

The session manager may require the following :

1. Location and linkage information for Personalization Server (or other) database.
2. APM related interface information (server URI).
3. Resource file locations
4. Session ID base
5. Log file URI
6. Default system time-out values

The following functions are available to the users of the session manager:

1. Session creation, which returns a unique session state object.
2. Session retrieval via session manager.
3. Put data into session - add an item to the session's property list, name-value pair, where value is an object.
4. Get data from a session - name-value pair property list.
5. Delete a value from a session.
6. Save a session state once the state has reached a new, consistent stage.
7. Destroy the current session, i.e., logout.

Internal methods:

1. Update of profile information - retrieval from personalization server.
2. Log-in to a given application (may use APM).
3. Log-out from a given application.
4. Get a new unique session id.

The session manager has to implement the

functionality described above by providing the following services:

1. Create a unique user session upon single sign-on from PIC.
- 5 2. Creation of a session, and retrieval of user profile data from personalization server database based on user credentials.
3. Association with a session-id, suited for passing, as post data over http to the devices and adaptors (must fit within thin client browser data size constraints).
- 10 4. Read-write access to session information via session id. This includes user profile, and dynamic session data.
- 15 5. Destruction of user session, through API call, or as a result of inactivity timeout.

The session manager also manages the following data:

- 20 1. Persistent user profile information: provisioned applications and associated devices supported, application specific generic workflows (MCML), sign-on enabling information (APM codes), PIC related preferences.
- 25 2. Non-persistent application session state and instance information. This data is application dependent and non-static. The EJB's that make up the application adaptors can use the session manager to store state and session information as required. This data is subject to inactivity timeout constraints.

The following design guidelines can apply:

- 35 1. The session manager is necessarily a high-demand service, and requires an efficient implementation, which would include caching, passivation and clustering support.

2. Java (Sun's JDK 1.2.2) is used for device and application adaptor coding.

3. WebLogic Server 5.1 provides the application server and container framework for these classes.

5. Weblogic Server's in-memory replication of HttpSession will be used to increase the throughput of session management. JDBC-based session management can also be considered in the future. The actual choice (in-memory replication vs JDBC) is transparent to the application layer (device adaptors and EJBs.)  
10 The Personalization Server (v 2.0) provides the Web-based PIC features upon which the multi-channel PIC (not described in this document) is based.

15 The session manager is ideally able to handle a large number of sessions concurrently, and must therefore use an efficient mechanism for data storage and retrieval. The limitations on performance are to be load tested and must concord with MASP specifications for number of concurrent multi-channel users.  
20

The DMI component or device adaptor (DA) can be implemented using the example provided below.

It should be noted that the example provided uses a PSTN telephone as the end user device.  
25

It should also be noted that the ASR/TTS (text-to-speech) channel functionality is dependent on the VoiceXML implementation.

Furthermore, since the voice channel has inherent limitations from a user-interface point of view, i.e.:  
30

- a) one-at-a-time menu selection capability,
- b) limited data entry capability,
- c) limited (to approximately 100 words) vocabulary  
35 for acceptable speaker-independent recognition.

The user interface for this implementation has some inherent problems. The user interacts with the system using DTMF tones and speech. Typically, the system prompts the user with generated and pre-recorded text and sounds, and the user can respond with DTMF keystrokes or with spoken commands. The interface is analogous interactive voice response (IVR) call flows, but the menus may be made "flatter" to take advantage of the larger response range of ASR as opposed to DTMF.

Some responses and prompts are standard for all applications, akin to the "\*", "0" or "#" DTMF request in an IVR system:

General guidelines:

- a. The user can say, "help" or "I don't understand", or "repeat" to obtain more information or an alternate prompt.
- b. Numeric responses can be entered via DTMF or ASR. Yes and No responses can be entered via DTMF as 1 or 2 respectively.
- c. The user can say "hang-up" to exit the application at any time.
- d. Passwords and PIN's should only be entered via DTMF to avoid being overheard or misinterpreted.

System requests:

- a) The system prompts the user with sounds, pre-recorded text, or TTS generated text, as indicated in the MCML flow.
- b) Failure to respond within a timeout setting in the session manager will result in the prompt be rephrased, and if no response is received after a longer timeout, the application will disconnect.

The multi-channel session manager maintains the end-user specific configuration. This

configuration information is used by the device adaptor to determine which applications are enabled for a particular user and channel.

5 Access to this information is through the session manager interface described elsewhere.

A single device adaptor is required for the ASR/TTS channel. Its role is to translate the MCML application flow into a state machine instance to drive the client.

10 The device adaptor is called from the PIC application when the user selects an application from the main menu.

The (DMI) component executes the following steps when accessing an application :

- 15 a) Start a selected application session, given the application name, and the APM key obtained from the PIC's login. The following steps are then taken:
- Logs-in to the selected application
  - If successful, this effectively starts a session for the user by calling the session manager to set-up an instance for the application session
  - Obtain the application's EJB coordinates for the application from the session manager
  - Obtains the MCML document from the session manager.
  - 25 - Translates the first state to a device specific template using the XSLT service and the device-specific style sheet.
  - Translate placeholders for dynamic content by making EJB calls.
  - 30 - Drive the application interaction including state transitions using EJB calls until the user exits the flow or a timeout occurs
  - Returns a status code to the calling application (PIC).
  - 35 a) Force an instance of a session to exit, based on



its session ID. Clean up any instance data in the session manager.

The design of the ASR/TTS component of the multi-channel subsystem involves two major sub-components:

a) The application adaptor, which consists of a set of Stateless Session Beans that communicate with the applications. The adaptor also consists of a MCML (XML multi-channel application flow) document that specifies the Finite State Machine (FSM) states that the adaptors require to implement the functionality specified.

b) The device adaptor, which drives the ASR/TTS engine VoiceXML implementation, in an application independent way.

Both these adaptors make use of underlying infrastructure services. These include the session manager, XSLT and XML related classes, and the application server's container framework classes.

The following design guidelines were used in this specific implementation :

1. Java (Sun's JDK 1.2.2) is used for device and application adaptor coding. Java extensions not in the standard distribution are based on the jars delivered with Web Logic.

2. Web Logic Server 5.1 provides the application server and framework for these classes (typically servlets). The Personalization Server (v 2.0) provides the Web-based PIC features upon which the multi-channel PIC (not described in this document) is based.

3. The device adaptors are application independent. The same device adaptor should work transparently with multiple applications. They implement specific

instances of the state machine described in the application-specific MCML documentation. Dynamic content generation links are contained in the MCML. It should be noted that the device adaptor is application independent. No assumptions about how the application flow can be made within that subsystem. This must be tested with different EJB's and MCML flows.

Furthermore, it should be clear that the MCML flows are necessarily device independent, in that they cannot depend on a client having certain capabilities beyond a common set of lowest common denominator controls, such as:

- Menus / selection lists;
- Accept and back buttons;
- Data entry fields, numeric, alphanumeric, and password; and
- Labels and prompts.

As mentioned above, the DA (device adaptor or DMI component) is implemented as a servlet and the AA's (application adaptors or AMI components) are implemented as EJB's. All calls (with an exception described below) are therefore remote object calls, and can return remote exceptions.

The DA can also call local utility classes either to facilitate application adaptation, or to allow more MCML functionality.

The DA is responsible for generating calls to AA methods under the guidance of the MCML script currently running. Since the calls to the AA's are generated dynamically, the called method signatures must be standardized. Additionally, the exception handling must be standardized to allow the DA to respond to business, system, and authentication errors.

The DA responds to exceptions in two distinct ways:

1. It catches non-authentication exceptions, and allows the MCML to take the failure branch in the script - potentially allowing another MCML block to handle the error appropriately.

1. Authentication exceptions cause the DA to call the AA's authentication methods, which is responsible for obtaining a user session with the application using the credentials stored in the session manager by the authentication servlet. There is a limit to the number of iterations the DA will try on a given authentication to avoid looping forever. Authentication exceptions are identified based on the returned string signature, which must contain a unique substring.

As an example of a DA servlet, the following source code implements a servlet which transforms an MCL document into VoiceXML.

```
/*
 *@version 1.0
 */
package com.nortel.masp.mca.servlet;
import java.io.*;
import javax.servlet.*;
import javax.servlet.http.*;
import java.util.*;
import com.icl.saxon.*;
import com.icl.saxon.output.*;
import com.icl.saxon.expr.*;
import org.xml.sax.*;
import com.nortel.masp.mca.MCML.*;
import com.nortel.masp.mca.stateManagement.*;
import com.nortel.masp.mca.util.*;
/**
```

\* VoiceServlet. Transforms a supplied MCML document  
into VoiceXML

\* using the supplied stylesheet xmlServlet.xsl

\*/

5  
public class VoiceServlet extends HttpServlet {  
 private static final String MCML\_VTABLE =  
 "maspMultiChannelAccessSessionMCMLVTACBLE";  
 private static final String  
10 DEFAULT\_LOGIN\_METHOD\_NAME\_KEY = "loginMethodName";  
 private static final String  
 DEFAULT\_INDEX\_MCML\_KEY = "defaultIndexMCML";  
 static private final String  
 DEFAULT\_ERROR\_HANDLING\_MCML\_KEY =  
15 "defaultErrorHandlingMCML";  
 static private final int debug = 1;  
 static private final int testVersion = 0;  
 static private final String INVALID\_USER\_MCML =  
 McaProperties.getInstance().getProperty("da.defaultIn  
20 validUserMCML", "mca/invaliduser.mcml");  
 static private final String ERROR\_HANDLING\_MCML =  
 McaProperties.getInstance().getProperty("da.defaultEr  
 rorHandlingMCML", "mca/errorhandler.mcml");  
 static private final String INDEX\_MCML =  
25 McaProperties.getInstance().getProperty("da.defaultIn  
 dexMCML", "mca/pic.mcml");  
 static private final String LOGIN\_METHOD\_NAME =  
 McaProperties.getInstance().getProperty("da.defaultLo  
 ginMethodName", "login");  
30 static private final String START\_BLOCK\_NAME =  
 "start";  
 static private final String BLOCK\_NAME = "\_b";  
 static private final String XML\_SOURCE = "\_x";  
 static private final String XSL\_STYLE = "\_l";  
35 static private final int MAX\_COUNT = 3;

```
static private final String CONTENT_TYPE =
"content-type";
static private final String MCA_HEADER =
"mcaheader";

5
static private final String XSL_EXT = ".xsl";
static private final String XML_EXT = ".mcml";
static private final String DEFAULT_APP_PATH =
McaProperties.getInstance().getProperty("da.defaultMC
10 MAppPath", "mca/");
/**
* doGet() - accept request and produce
response<BR>
* URL parameters: <UL>
15 * <li>_x - URL of source document</li>
* <li>_l - URL of stylesheet</li>
* <li>clear-stylesheet-cache - if set to yes,
empties the cache before running.
* <li>URL format:
20 /demo?uniqueID?_x=xxx.mcml?_l=xxx.xsl?_b=start
* </UL>
* @param req The HTTP request
* @param res The HTTP response
*/
25 public void doGet(HttpServletRequest req,
HttpServletResponse res)
throws ServletException, IOException
{
doPost(req, res);
30 }
/**
* doPost() - accept request and produce
response<BR>
* URL parameters: <UL>
35 * <li>_x - URL of source document</li>
```

```

    * <li>_1 - URL of stylesheet</li>
    * <li>clear-stylesheet-cache - if set to yes,
    empties the cache before running.
    * </UL>
5    * @param req The HTTP request

    * @param res The HTTP response
    */
    public void doPost(HttpServletRequest req,
10    HttpServletResponse res)
        throws ServletException, IOException
    {
        Log.log(Log.DEBUGGING, this.getClass(),
        PrintUtil.convertToString(req));
15        String source = null;
        /*req.getParameter(XML_SOURCE);*/
        String style = null;
        /*req.getParameter(XSL_STYLE);*/
        String blockname = null;
20    /*req.getParameter(BLOCK_NAME);*/
        String querystr = req.getQueryString();
        SessionStateManagerDef manager =
        SessionStateManagerAbstractFactory.makeManager(req,
        res);
25        SessionState state = null;
        SessionState tmpState = new
        SessionState("tmpawewe2336623233");
        boolean bInvalidUser = false;
        // Check if the session is created or not.
30        if (!manager.isSessionStarted())
        { // Create a new session and initialize
        it.
            initSession(manager);
        }
35        state = manager.getCurrentState();
    }
```

```
if (state == null)
{
    Log.log(Log.ERROR, getClass(), "state
5    == null");
    bInvalidUser = true;

    state = tmpState;
}
SessionState    varTable =
10    getVarTable(state);
    String sessionKey = state.getSessionKey();
    Log.log(Log.DEBUGGING, getClass(),
    "SessionKey = " + sessionKey);
    Log.log(Log.DEBUGGING, getClass(),
15    "QueryString::" + querystr);
    String cururl0;
    String absURL =
    req.getParameter("absoluteURL");
    String hostURL = req.getScheme() + "://" +
20    req.getServerName() + ":"
                                + req.getServerPort() +
    req.getServletPath();
    if (absURL != null && absURL.equals("1"))
    {
25        cururl0 = hostURL;
    }
    else
    {
        cururl0 = req.getServletPath();
30    }
    cururl0 = manager.encodeURL(cururl0);
    hostURL = manager.encodeURL(hostURL);
    Log.log(Log.DEBUGGING, getClass(),
    "##### New version Servlet ....My Current URL2 = "
35    + cururl0);
```

```
String id = null; // temporary id for test
only =====

    ParameterSet params = new ParameterSet();
5    // Check if there is a '?' in cururl0
    params.put("id", new
StringValue(generateId()));
    varTable.put("url", hostURL);
    ServletOutputStream out =
10    res.getOutputStream();
    Enumeration p = req.getParameterNames();
    while (p.hasMoreElements())
    {
        String name = (String)p.nextElement();
15        String value = req.getParameter(name);
        if (name.equals(XML_SOURCE))
        {
            source = value;
            String tmp = null;
20            try
            {
                tmp =
(String)varTable.get(XML_SOURCE);
            }
25            catch(Exception e)
            {
                tmp = null;
            }
            if (tmp != null)
30            {
                if
(source.equals((String)varTable.get(XML_SOURCE)))
                    continue;
            }
35        }
    }
```



```
else if (name.equals(XSL_STYLE))
{
    style = value;
    String tmp = null;
5    try

    {
        tmp =
10    (String)varTable.get(XSL_STYLE);
    }
    catch(Exception e)
    {
        tmp = null;
    }
15    if (tmp != null)
    {
        if
20    (style.equals((String)varTable.get(XSL_STYLE)))
        continue;
    }
}
else if (name.equals(BLOCK_NAME))
{
    blockname = value;
25    // do not put the blockname into
parameterset until we start XSLT
    continue;
}
else if
30 (name.equals("clear-stylesheet-cache"))
{
    if (value.equals("yes"))
        clearCache();
}
35 if (value != null)
```

```

        {
            params.put(name.intern(), new
StringValue(value));
            Log.log(Log.DEBUGGING, getClass(), name
5      + "=" + value);

            varTable.put(name, value);
        }
        else
10      Log.log(Log.DEBUGGING, getClass(), name
+ " does not have its value.");
    }

    if (blockname == null && source == null)
        source = INDEX_MCML;
15    if (source == null)
    {
        try
        {
            source =
20      (String) varTable.get(XML_SOURCE);
        } catch (Exception e)
        {
            source = INDEX_MCML;
        }
25      params.put(XML_SOURCE, new
StringValue(source));
        varTable.put(XML_SOURCE, source);
    }

    if (style == null)
30  {
        try
        {
            style =
35      (String) varTable.get(XSL_STYLE);
        }
    }
}

```

```

        catch (Exception e)
        {
            // temporarily code
            #####
5            style = "html";

            Log.log(Log.DEBUGGING,
getClass(), "XSL style sheet is not found. Using
html.xsl as default!");
10        }

        params.put(XSL_STYLE, new
StringValue(style));
        varTable.put(XSL_STYLE, style);
    }
15    if (blockname == null)
    {
        blockname = START_BLOCK_NAME;
        //source = INDEX_MCML;
        //varTable.put(XML_SOURCE, source);
20        Log.log(Log.DEBUGGING, getClass(),
"blockname == null, use start as block-name");
        //params.put(BLOCK_NAME, new
StringValue(START_BLOCK_NAME));
    }
25    if (style.indexOf("vxml") >= 0)
        cururl0 = hostURL;
    if (cururl0.indexOf("?") < 0)
        cururl0 = cururl0 + "?_dmy=1";
    Log.log(Log.DEBUGGING, getClass(),
30    "=====cururl0
=====\\n" + cururl0

+

"\\n=====cururl0
=====");
35    params.put("cururl0", new

```

String value(cururl0));  
int innerCount = 0;  
int outCount = 0;  
do  
5 {  
  
outCount ++;  
bInvalidUser = false;  
try  
10 {  
// Run the MCML filter to get the  
specified MCML block according to the given block  
name  
String mcmlText = null;  
do  
15 {  
innerCount ++;  
bInvalidUser = false;  
logMsg("source =" + source);  
logMsg("\_b =" + blockname);  
20 String path;  
if (source.indexOf(".mcml") >= 0) {  
path =  
getServletContext().getRealPath(DEFAULT\_APP\_PATH +  
25 source);  
else  
path =  
getServletContext().getRealPath(DEFAULT\_APP\_PATH +  
source + XML\_EXT);  
30 MCMLFilter mcmlFilter = new  
MCMLFilter(path, blockname, manager); //varTable);  
try  
{  
mcmlText = mcmlFilter.run();  
35 }  
}

```

        catch (InvalidUserException e)
        {
            Log.log(Log.ERROR,
2           getClass(), e);
            // Invalid user

            bInvalidUser = true;
            source = INVALID_USER_MCML;
            blockname =
10         START_BLOCK_NAME;
        }
        catch (NoBlockException e)
        {
            Log.log(Log.ERROR,
15         getClass(), e);
            bInvalidUser = true;
            source =
            ERROR_HANDLING_MCML;
            blockname =
20         START_BLOCK_NAME;
        }
        catch (UserDefinedBlockException e)
        {
            String gotoStr =
25         e.toString().substring(e.toString().indexOf(":") +
            1).trim();
            System.out.println("#####UserDefined
            Block
            handling#####
30         #####");
            System.out.println(gotoStr);
            System.out.println("#####
            #####");
            StringTokenizer gotoParams =
35         new StringTokenizer(gotoStr, "&");

```

```

        params.clear();
        params.put("cururl0", new
StringValue(cururl0));
            params.put("id", new
5   StringValue(generateId()));

                String prevSource = source;
                String prevBlockname =
blockname;
10         while
           (gotoParams.hasMoreTokens())
               {
                   StringTokenizer
oneParamToken = new
15     StringTokenizer(gotoParams.nextToken(), "=");
                        String name =
oneParamToken.nextToken();
                                String value = null;
                                    if
20      (oneParamToken.hasMoreTokens())
                                        {
                                            value =
oneParamToken.nextToken();
                                                }
25                                     if
                                           (name.equals(XML_SOURCE))
                                               {
                                                    source =
value;
30                                                         String tmp =
null;
                                                                    try
                                                                        {
                                                                            tmp =
35    (String)varTable.get(XML_SOURCE);
```

```

    }
    catch(Exception re)
    {
        tmp =
5      null;

        }
        if (tmp !=
10      null)
        {
            if
            (source.equals((String)varTable.get(XML_SOURCE)))
            continue;
        }
15      }
        else if
        (name.equals(XSL_STYLE))
        {
            style =
20      value;
            String tmp =
            null;

            try
            {
25      (String)varTable.get(XSL_STYLE);
                tmp =

            }
            catch(Exception re)
            {
30      tmp =
            null;

            }
            if (tmp !=
35      null)
            {
```

```

                                                                    if
        (style.equals((String)varTable.get(XSL_STYLE)))
        continue;
5
    }

    else if
        (name.equals(BLOCK_NAME))
    {
10
        blockname =
        value;

        // do not put
        the blockname into parameterset until we start XSLT
        innerCount =
15
        0;

        bInvalidUser
        = true;

        continue;
    }
20
    varTable.put(name,
    value);
    params.put(name.intern(), new StringValue(value));
    }
    if (!bInvalidUser ||
25
        (prevBlockname.equals(blockname) &&
        prevSource.equals(source)))
        throw new Exception();
    }
    catch(Exception e)
30
    {

        Log.log(Log.ERROR,
        getClass(), e);

        bInvalidUser = true;
        source =
35
        ERROR_HANDLING_MCML;
```



```
blockname =  
START_BLOCK_NAME;  
    }  
    } while (bInvalidUser && innerCount <  
5 MAX_COUNT);
```

```
10     if (innerCount >= MAX_COUNT)  
    {  
        innerCount = 0;  
        throw new Exception("Block (" +  
            blockname + ") is not found in " + source);  
    }  
15     params.put(BLOCK_NAME, new  
        StringValue(blockname));  
        varTable.put(BLOCK_NAME, blockname);  
        apply(style, mcmlText, params, req,  
20 res, state) ;  
    }  
    catch(Exception e)  
    {  
        varTable.put("_errorString",  
25 e.toString());  
        Log.log(Log.ERROR, getClass(), e);  
        if  
            (source.indexOf(ERROR_HANDLING_MCML) >= 0)  
            bInvalidUser = false;  
        else  
30 {  
            bInvalidUser = true;  
            source = ERROR_HANDLING_MCML;  
            blockname = START_BLOCK_NAME;  
            params.clear();  
35 params.put("cururl0", new
```

```

        StringValue(cururl0));
                                params.put("id", new
        StringValue(generateId()));
                                params.put(XML_SOURCE, new
5      StringValue(source));

                                params.put(XSL_STYLE, new
        StringValue(style));
                                //params.put(BLOCK_NAME, new
10     StringValue(blockname));
                                }
                                }
                                //params = createNewParams(blockname);
                                } while (bInvalidUser && outCount <
15     MAX_COUNT);
                                manager.saveState();
                                }
                                private void initSession( SessionStateManagerDef
        manager)
20     {
                                manager.startSession();
                                SessionState state =
        manager.getCurrentState();
                                state.put(DEFAULT_LOGIN_METHOD_NAME_KEY,
25     LOGIN_METHOD_NAME);
                                state.put(DEFAULT_INDEX_MCML_KEY,
        INDEX_MCML);
                                state.put(
        DEFAULT_ERROR_HANDLING_MCML_KEY,
30     ERROR_HANDLING_MCML);
                                }
                                /**
                                * getServletInfo<BR>
                                * Required by Servlet interface
35     */

```

```
public String getServletInfo() {
    return "Calls SAXON to apply a stylesheet to
a source document";
}
5    /**
    * Apply stylesheet to source document
    */
    private void apply(String style, String source,
10        ParameterSet params,
        HttpServletRequest req,
        HttpServletResponse res,
        SessionState varTable)
        throws SAXException, java.io.IOException
15    {
        ServletOutputStream out =
        res.getOutputStream();
        if (style==null)
        {
20            out.println("No style parameter
            supplied");
            return;
        }
        if (source==null)
25        {
            out.println("No source parameter
            supplied");
            return;
        }
30        try
        {
            StringWriter strout = new
            StringWriter();
            PrintWriter pout = new
35            PrintWriter(strout);
```

```
try
{
    String contentType =
5  (String)varTable.get(CONTENT_TYPE);

    String mcaHeaderFileName =
    (String)varTable.get(MCA_HEADER);
    String mcaFilePath =
    getServletContext().getRealPath(DEFAULT_APP_PATH +
10  mcaHeaderFileName);

    FileReader in = null;
    try
    {
        in = new
15  FileReader(mcaFilePath);
    }
    catch(FileNotFoundException e)
    {
        varTable.put("_errorString", e.toString());
20        throw e;
    }
    BufferedReader bufIn = new
    BufferedReader(in);

    // Read the header
25  String rdln;
    while ((rdln =
    bufIn.readLine()) != null)
    {
        pout.println(rdln);
30    }

    // set content type
    res.setContentType(contentType);
}
catch (Exception e)
35  { // If there is no content-type
```

```

passed from sessionState, we hardcode it here.
////////////////////////////////////
////////////////////////////////////

        Log.log(Log.DEBUGGING, getClass(),
5      "##### content-type and mcaheader from auth
      servlet are not correctly" );

        if (style.indexOf("vxml") >= 0)
        {
10              pout.println("<?xml
version=\"1.0\"?>");

        res.setContentType("text/vxml");
        //setContentType("text/vnd.wap.wml");
15              }
              else if (style.indexOf("wml") >= 0)
              { // for wml
                    pout.println("<?xml
version=\"1.0\"?>");
20              pout.println("<!DOCTYPE wml
PUBLIC \"-//WAPFORUM//DTD WML 1.1//EN\"
\"http://www.wapforum.org/DTD/wml_1.1.xml\">");
        res.setContentType("text/vnd.wap.wml");
        //setContentType("text/vnd.wap.wml");*/
25      /*setContentType(details.getMediaType());
              }
              else if (style.indexOf("html") >= 0)
              { // for html
                    pout.println("<?xml
30      version=\"1.0\"?>");

                    pout.println("<!DOCTYPE wml
PUBLIC \"-//WAPFORUM//DTD WML 1.1//EN\"
\"http://www.wapforum.org/DTD/wml_1.1.xml\">");
        res.setContentType("text/x-wap.wml");
35      //setContentType("text/vnd.wap.wml");

```

```

        setContentType(details.getMediaType());
    }
    else
    {
5      res.setContentType("text/html");
      //setContentType("text/vnd.wap.wml");
      setContentType(details.getMediaType());
    }

10  //////////////////////////////////////
  //////////////////////////////////////
    }
    PreparedStyleSheet pss =
5    tryCache(style);
    StyleSheetInstance ssi =
    pss.makeStyleSheetInstance();
    OutputDetails details =
    pss.getOutputDetails();
0    details.setWriter (pout);
    ssi.setOutputDetails(details);
    ssi.setParams(params);
    Log.log(Log.DEBUGGING, getClass(),
    "The input MCML as follows\n" +
5    "=====MCML
    BEGINNING=====\\n" +
    source + "\\n" +

    "=====MCML END=====\\n"
    );
    StringReader sourceReader = new
    StringReader(source);
    ssi.transform(new
    ExtendedInputSource(sourceReader));
    String xmlstr;

```

```
xmlstr = strout.toString();
pout.close();
sourceReader.close();
Log.log(Log.DEBUGGING, getClass(),
5
        "====The result
after XSLT =====\n"

        + xmlstr
10      +
"\n=====END=====");
        PostProcess postProc = new
PostProcess(req, res, varTable);
        try
15      {
            postProc.run(xmlstr);
        }
        catch (ServletException err)
        {
20      res.getOutputStream().println("Error MethodProcess: "
+ err.getMessage());
        }
    }
    catch (SAXException err)
25      {
        throw err;
//out.println(err.getMessage());
    }
}

30      // first get unique ID from URL
        // if there is no id=XX, it means this
request is from a new session
        // if there is an id, then try to llok up
MCMLVariables table, if the
35      // table is not found. The request is
```

```
    treated as a new request.
    /*
    */
    public SessionState getVarTable(SessionState
5    state)
    {
        if (testVersion == 0)

            return state;
10        else

            return gMCMLtable;

    }
    /**
    * Maintain prepared stylesheets in memory for
15    reuse
    */
    private synchronized PreparedStyleSheet
    tryCache(String url) throws SAXException {
        String path;
20        if (url.indexOf(".xsl") >= 0)
            path =
            getServletContext().getRealPath(DEFAULT_APP_PATH +
            url);
        else
25            path =
            getServletContext().getRealPath(DEFAULT_APP_PATH +
            url + XSL_EXT);
        if (path==null)
        {
30            throw new SAXException("Stylesheet " +
            path + " not found");
        }
        PreparedStyleSheet x =
        (PreparedStyleSheet) cache.get(path);
35        if (x==null)
```



```

    {
        x = new PreparedStyleSheet();
        x.prepare(new ExtendedInputSource(new
5      File(path)));
        cache.put(path, x);
    }
    return x;
}

10      private void logMsg(String logInfo)
    {
        Log.log(Log.DEBUGGING, getClass(),
logInfo);
    }
15      private synchronized String generateId()
    {
        Date tm = new Date();
        Long ln = new Long(tm.getTime());
        return ln.toString();
20      }

    /**
     * Clear the cache. Useful if stylesheets have
     * been modified, or simply if space is
     * running low. We let the garbage collector do
25  the work.
    */
    private synchronized void clearCache()
    {
        cache = new Hashtable();
30      }

    private static SessionState gMCMLtable = new
SessionState("12345676878999");
    private Hashtable cache = new Hashtable();

35  }
```

To create proper EJB's which can be called from a DA, the following guidelines apply :

1) All EJB methods must have the following signature:

5       String EJBMethodName(SessionStateManagerDef  
      manager, Properties params)  
      throws CreateException, RemoteException,  
RemoveException

Error handling:

10      The Device Adaptor uses two ways to check whether the  
EJB call fails:

      Catch an exception from the EJB method  
      Check if the return value is null

15      Parameter passing:

      The method should get its associated  
parameters from the params Properties according to  
its corresponding parameter name. An alternate  
mechanism for data passing between method calls is to  
20      use the SessionStateManager to store state data  
between calls.

The following example illustrates the latter for  
getting a username and password:

      SessionState state;  
25      state = manager.getCurrentState();  
      String username = (String)state.get("username");  
      String password = (String)state.get("password");

2) Each application EJB must implement an  
30      authentication method. The signature is as follows:

String login(SessionStateManagerDef manager,  
Properties params)  
throws CreateException, RemoteException,  
35      RemoveException

This method is be called by the DA if the EJB method fail to find an active session in the Session State, as a result of the session manager throwing an exception which is passed up to the DA.

5

3) The proper MCML Syntax for making EJB or Class method call must be followed.

The following MCML block gives an example of a call to the getSummaries in CalendarEJB

```

10      <block blocktype="UserDefinedBlock"
      blockname="getsummaries">
          <properties/>
          <action>
      15      <method name="getSummaries" type="ejb"
      interface="com.nortel.masp.mca.CalendarRemote"
      jndi="mca.CalendarHome"> <params>
          <param
      name="applicationURL=http://wleey006.ca.Nortel.com"
      type="text"/>
      20      <param name="port=81"
      type="text"/>
          <param name="date" type="text"/>
          </params>
          <result name="summariesmenu"/>
      25      </method>
          </action>
          <nextblocks>
              <success goto="saysummaries"/>
              <failure goto="noappointment"/>
      30      </nextblocks>
          </block>

```

The "interface" attribute in the method element specifies the remote interface of an EJB. The "jndi" attribute specifies the JNDI\_NAME for the EJB.

35 To create classes which are callable from the DA

through the MCML scripts (or broker modules), the following guidelines apply :

The DA may be used to invoke non-EJB classes, that can serve to enhance its functionality.

5 These classes are called under the control of an MCML script, in the same way as an AA is called.

These classes must follow the rules below:

1) The methods must handle all the exception internally. The DA does NOT catch any exceptions  
10 thrown.

2) The methods only have one input parameter - Properties params.

All the parameter the method needs have to get from the passed properties.

15 For example: toSpeakableDate() is in the com.Nortel.masp.mca.MCML.MCMLutils class and is defined as follows:

```
public String toSpeakableDate(Properties params)
{
20     String theDateStr = params.getProperty("date");
    String theReturnStr = null;
    ..
    return theReturnStr;
}
```

25 The associated MCML required is as follows:

```
<block blocktype="MenuBlock"
blockname="verifydate">
    <action>
<method name="toSpeakableDate"
30 interface="com.nortel.masp.mca.MCML.MCMLutils">
    <params>
        <param name="date" type="text"/>
    </params>
    <result name="speakableDate"/>
35 </method>
```

```

        </action>
        <prompt>
            <message msgtype="text" content="Your
entered date is {$speakableDate}."/>
5      <message msgtype="text" content="If it is correct,
please say yes, otherwise say no."/>
        </prompt>
        <menuitems>
            <menu title="yes" id="yes"/>
10      <menu title="no" id="no"/>
        </menuitems>
        <choices>
            <nextblock id="yes"
goto="getsummaries"/>
15      <nextblock id="no"
goto="askfordate"/>
        </choices>
    </block>
    An example of a simple MCML workflow that includes
20  an EJB call action is provided below : ( test.mcml)
    <?xml version= "1.0"?>
    <mcml>
        <FSMFlow>
            <block blocktype="UserDefinedBlock"
25  blockname="start">
                <action>
                    <method name="getSummaries" type="ejb"
interface="com.nortel.masp.mca.MyCalendarRemote"
jndi="mca.MyCalendarHome">
30      <params>
                        <!--param
name="remote=com.nortel.masp.mca.CalendarRemote"
type="text"/-->
                                <!--param
35  name="jndi=mca.CalendarHome" type="text"/ -->

```

```

    <param
name="CalendarURL=http://wleey006.ca.nortel.com"
type="text"/>
    <param name="port=81"
5    type="text"/>
    <param name="username=demo"
type="text"/>
    <param name="password=new2day"
type="text"/>
10    <param name="date" type="text"/>
    </params>
    <result name="summariesmenu"/>
    </method>
    </action>
15    <nextblocks>
        <success goto="saysummaries"/>
        <failure goto="saynoappointment"/>
    </nextblocks>
    </block>
20    <block blocktype="DisconnectBlock"
blockname="disconnect">
        <disconnect/>
    </block>
    </FSMFlow>
25 </mcml>

```

Regarding the application adaptor or the AMI component, an example is provided which utilizes the Calendar, E-mail and Contact List as the application.

30           These applications may have the following capabilities :

Calendar Express:

•get appointment summaries for a given date  
35 incrementally (limited by client's buffer size)

-get details (location, start, end, summary, text)  
for a given appointment based on start time  
- set an appointment for a given date and time using  
standard locations and summaries

5

E-mail:

- a) indicate how many unread messages you have
- b) set current mailbox
- get summary lines (headers) and message ids for  
unread or for all messages in a mailbox incrementally  
(limited by client's buffer size)
- d) get message text based on message id or next  
message in a mailbox or next unread message
- e) delete the current message (akin to voice mail  
deletes on the current message)
- f) send standard reply to a message based on message  
id

Contact list:

- get contact list incrementally (limited by client's  
buffer size)
- get detail information for a given contact name
- send a standard message to a person in the contact  
list
- prepare a receiver list for an e-mail based on the  
contact list
- add the sender's name to the contact list based on a  
received e-mail id number

This example assumes that the application  
session is available to the adaptor through a session  
id mechanism described elsewhere. Also, the example  
assumes the following :

Populating fields in the session manager's  
database does the application and user provisioning.

•The standards based API's used here to interface with the email application (SMTP and IMAP4)

•No special client software is assumed (or indeed possible in most cases) on the target. Since some channels may have inherent limitations from a user-interface point of view, i.e.:

- a) one-at-a-time menu selection capability,
- b) data entry capability is limited (to approximately 100 words) vocabulary for acceptable speaker-independent recognition

The session manager described above has, relative to the application adaptor, the following functions :

1. Maintains the end-user specific configuration.
2. User authentication into the application. Using a session id, the application adaptors can use the session manager to access applications, using existing sub-systems like APM.
3. Dynamic session instance management. The session manager can be used to store dynamic session state information on behalf of the application adaptor. The "handle" into that state information is the session id, obtained through the PIC.
4. User profile management. Profiles are created and populated via the MIC and BIC interface in the completed system, but would be manually populated for the interim release checkpoints, and for testing purposes. Web-based provisioning is assumed to be as provided by MASP 1.1. Examples of configuration fields on a per-user basis would consist of:



- a) Predefined (by user) e-mail responses;
- b) Predefined (by user) appointment summaries and locations;
- c) List of enabled applications, and URI's on a per-channel basis;
- d) Time-out values for application access;
- e) Application specific instance fields (containers). For example "session-id".

To access the applications, the application  
adaptors must accomplish the following :

Application : Calendar:

Functions :

- a) Get appointment summaries (headers) based on session id and date
- b) Get appointment detail, based on session id, appointment date and time
- c) Set an appointment, based on session id, appointment date and time, and input appointment data fields

Application : e-mail

Functions:

- a) Set a mailbox to be current based on session id, and mailbox id
- b) Get the number of unread messages in all mailboxes, or in the specified mailbox, based on session id and mailbox name.
- c) Get message summaries, based on session id, mailbox name. Get summaries for all messages (unless unread-only flag is set). Provision to do this incrementally is provided to account for device buffer limitations.

Application : Contact List:

## Functions :

- 5                   a) Get names in contact list  
                    incrementally based on session id, and  
                    number of entries (limited by client's  
                    buffer size)  
                    c) Get detail on a given name, based  
                    on session id and contact name  
                    d) add a name to the contact list  
                    based session id and contact name

10

As noted above, the application adaptor consists of a set of Stateless Session Beans that communicate with the applications. The broker module consists of a MCML (XML multi-channel application flow) document that specifies the Finite State Machine (FSM) states that the application adaptors require to implement the functionality specified.

15                   The device adaptors use the application  
                    adaptors to present device-specific drives the ASR-  
20                   TTS engine (VoicePortal), in an application  
                    independent way.

The application adaptors described here are implemented as Stateless Session Enterprise Java Beans deployed within a Java-based application server, and communicate with the target applications on the "back-end". The EJB's abstract the application interface presented to the device adaptors and are written once per application such that different device adaptors without modification may use them.

25                   The user's flow through the application is  
30                   guided by the broker module which is an MCML (multi-  
                    channel mark-up language) XML document that contains  
                    references to the EJB's. It is the MCML document  
                    that guides the device adaptor in its sequence of  
35                   calls to the EJB's, which are effectively action

methods used to generate dynamic content for the application flow.

In this example, the following design guidelines were applied :

- 5           1. Java (Sun's JDK 1.2.2) is used for device and application adaptor coding.
2. The J2EE 2.0 specification for EJB interface and deployment is adhered to.
3. Web Logic Server 5.1 provides the application server and container framework for these classes. The Personalization Server (v 2.0) provides the Web-based PIC (Personal Interaction Portal) features upon which the multi-channel PIC is based.
- 10           4. The application adaptor EJB's are stateless, in that any device-side method call can be made at any time. State is maintained outside the EJB's, in the unique Session Manager. Therefore EJB's can be replicated and clustered.
5. The device adaptors are application independent. The same device adaptor should work transparently with multiple applications. They implement specific instances of the state machine described in the application-specific MCML document - see below.
- 20           6. The application's workflow is contained within the MCML document that can be obtained by calling the application's EJB. This flow describes a set of states and associated controls and actions that the device adaptor can choose to implement.
7. All EJB's must use the session manager to store state or instance information. No
- 35

instance variables are allowed. The EJB's should be clusterable across different servers and operate with a single logical session manager.

5           The following code is that of a Java bean for the calendar application

/\*\*

10       \* CalendarBean -- implement the methods in this  
      \* interface as well as providing  
      \* the implementation of the business methods.  
      \*  
      \* @version 1.0  
      \*/  
15       package com.nortel.masp.mca.ejb;  
      import javax.ejb.\*;  
      import java.rmi.Remote;  
      import java.rmi.RemoteException;  
      import javax.naming.InitialContext;  
20       import javax.naming.NamingException;  
      import java.io.\*;  
      import java.util.\*;  
      import java.text.\*;  
      import java.net.URL;  
25       import com.nortel.masp.mca.stateManagement.\*;  
      import com.nortel.masp.mca.util.\*;  
      import com.nortel.masp.mca.MCML.XMLTranslator;  
      //import org.xml.sax.\*;  
      //import org.xml.sax.helpers.\*;  
30       public class MyCalendarBean implements SessionBean{  
          static private String SESSIONID =  
          "CalendarSessionUserIDCLIENT";  
          static private String CONNECTURLSTR =  
          "CalendarSessionConnectionURLStringCLIENT";  
35       static private String CALENDARID =

```
"CalendarUserIDCLIENT";
    static private String USERNAME =
Constants.MCA_USERID_KEY;
    static private String PASSWORD =
5 Constants.MCA_PASSWORD_KEY;
    static private String APPURL =
Constants.MCML_APPURL_TAG;

    static private String PORT = "port";
10    static private String DATE = "date";
    static private String EVENTID = "eventid";
    static private String[] monthStr={"January",
"February", "March", "April", "May", "June", "July",
"August", "September",
15    "October", "November", "December"};
    static private int m_GMT_offset = -5; //
Eastern time of Canada
    private SessionContext ctx = null;
    private String userSessionId = null;
20    private boolean loginSucceed;
    private boolean logoutSucceed;
    private String url;
    private String port;
    private String curDate;
25    private String calendarId;
    private boolean bhasEvent;
    public void ejbActivate(){
        log("CalendarBean activated");
    }
30    public void ejbRemove(){
        log("CalendarBean Removed");
        // logout of Calendar
    }
    public void ejbPassivate(){
35        log("CalendarBean Passivate");
```

```

    }
    /**
     * Sets the session context.
     *
     * @param SessionContext
     */
    public void setSessionContext(SessionContext
context){

10        log("CalendarBean Context set");
        ctx = context;
    }

    public void ejbCreate() throws CreateException {
    }

15    public String
getSummaries(SessionStateManagerDef manager,
Properties params)
    {
        log("#####getSummaries() Inside
20    EJB#####");

        SessionState state =
manager.getCurrentState();

        String theDate =
params.getProperty("DATE");

25        Calendar localTime =
Calendar.getInstance(TimeZone.getDefault());

        Integer year, month, day;

        int curYear =
localTime.get(Calendar.YEAR); // because the default
30    year from VXML is 2001

        year = new Integer(curYear);
        ///Integer( theDate.substring(0, 4));

        month = new Integer(
theDate.substring(4, 6));

35        day = new Integer(

```

```

theDate.substring(6, 8));
//          System.out.print("year = ");
//          System.out.print("month = ");
//          System.out.print("day = ");
5      sessionId =
      (String)state.get(SESSIONID);
      log(SESSIONID + "=" + sessionId);
      url =
      (String)state.get(CONNECTURLSTR);
10
      bhasEvent = false;
      String retStr =
      getSummaries(year.intValue(), month.intValue(),
      day.intValue());
15      log("Result:");
      log(retStr);
      if (!bhasEvent)
          retStr = null;
      if (retStr != null)
20      {
          XMLTranslator translator =
          new XMLTranslator();
          try
          {
25              retStr =
              translator.translate(retStr, "calsummary.xml");
              log("MCML output:");
              log(retStr);
          }
30      catch(Exception e)
      {
          retStr = null;
          e.printStackTrace();
      }
35  }

```

```
log("#####End of
getSummaries() Inside EJB#####");
return retStr;
}
5    public String getDetail(SessionStateManagerDef
manager, Properties params)
    {
//log("#####getDetail() Inside
EJB#####");
10
        SessionState state =
manager.getCurrentState();
        String theDate =
params.getProperty(DATE);
15        userSessionId =
(String)state.get(SESSIONID);
        //log(SESSIONID + "=" +
userSessionId);
        url =
20    (String)state.get(CONNECTURLSTR);
        String eventId =
(String)params.get("UID");
        calendarId =
(String)state.get(CALENDARID);
25        log("UID = " + eventId);
        bhasEvent = false;
        String retStr =
getEvent(userSessionId, eventId);
        log("Result:");
30        log(retStr);
        if (!bhasEvent)
            retStr = null;
        if (retStr != null)
        {
35            XMLTranslator translator =
```



```
new XMLTranslator();

        try
        {
            retStr =
5      translator.translate(retStr, "caldetail.xml");
            log("MCML output:");
            log(retStr);
        }
        catch(Exception e)
10      {
            retStr = null;
            e.printStackTrace();
        }
15      }

      log("#####End of
getDetail() Inside EJB#####");
      return retStr;
    }

20    public boolean login(SessionStateManagerDef
manager, Properties params)
    {
        SessionState state =
manager.getCurrentState();
25        String username =
params.getProperty(USERNAME);
        if (username == null)
            username =
        (String)state.get(USERNAME);
30        String password =
params.getProperty(PASSWORD);
        if (password == null)
            password =
        (String)state.get(PASSWORD);
35        String port =
```

```

params.getProperty(PORT);
        String appURL = null;
        try
        {
5             appURL =
            (String)state.get(APPURL);
                log("appUrl = " + appURL);
        }
        catch(Exception e)
10         {

                appURL = null;
            }
            if (appURL == null)
15                 appURL
=params.getProperty(APPURL);
                log("appUrl = " + appURL);
                URL myUrl = null;
                try
20                 {

                        myUrl = new URL(appURL);
                    }
                //catch(MalformedURLException e)
                catch(Exception e)
25                 {

                        e.printStackTrace();
                        return false;
                    }
                port = toString(myUrl.getPort());
30                 appURL = myUrl.getProtocol() + "://"
+ myUrl.getHost();
                boolean bRet = login(appURL, port,
username, password);
                if (bRet)
35                 {

```

```

state.put (SESSIONID,
userSessionId);

state.put (CONNECTURLSTR,
url);
5 state.put (CALENDARID,
calendarId);

} else {
int at =
username.indexOf("@");
10 if( at > 0) {

username =
username.substring( 0, at );
15 bRet = login(appURL,
port, username, password);

if(bRet) {
state.put(SESSIONID, userSessionId);
state.put(CONNECTURLSTR, url);
20 state.put(CALENDARID, calendarId);

}

}

Log.log(Log.DEBUGGING, getClass(),
25 "##### iPlanet Username =" +
username + "#####");

return bRet;

}

/**
30 * Get a specific day's summaries from
00:00:00 -> 23:59:59
* @param int year
* @param int month
* @param int day
35 */

```

```
private String getSummaries(int year, int month,
int day ){
    log("userSessionID = " + userSessionId);
    System.out.print("year=");
5   System.out.print(year);
    System.out.print("month=");
    System.out.print(month);
    System.out.print("day=");
    System.out.print(day);
10   String strRetrieveSummary =
    retrieveSummaryString(userSessionId, year, month,
    day);

    return urlConnection(strRetrieveSummary,
15   "Summary");
}

/**
 * Get a specific event based on session ID
and event ID
20   * @param String session ID
    * @param String event ID
    */

    private String getEvent(String sessionId, String
eventId){
25   String strEvent = eventString(sessionId,
eventId);
    return urlConnection(strEvent, "Event");
}

//http://wleey006:81/login.wcap?user=wbin&password=ne
30   w2day&refresh=1&fmt-out=text/xml

    private String loginString(String url, String
port, String user, String password){
    StringBuffer buffer = new
StringBuffer(url);
35
```

```
buffer.append(":").append(port).append("/login.wcap?"
);
buffer.append("user=").append(user).append("&").append
d("password=").append(password);
5  buffer.append("&refresh=1&fmt-out=text/xml");
    return buffer.toString();
    }
    //
http://wleey006:81/fetchevents_by_id.wcap?id=sessionI
10 d&uid=eventId&rid=0&mod=1&calid=wbin&brief=0&fmt-out=
text/xml
    private String eventString(String sessionId,
String eventId) {

15         StringBuffer buffer = new
StringBuffer(url);
buffer.append(":").append(port).append("/fetchevents_
by_id.wcap?");
buffer.append("id=").append(sessionId).append("&").ap
20 pend("uid=").append(eventId);

buffer.append("&rid=0").append("&mod=1").append("&cal
id=").append(calendarId);

25         buffer.append("&brief=0&fmt-out=text/xml");

        return buffer.toString();
    }
//http://wleey006:81/logout.wcap?id=n32nv9q3b2r5po32o
30 q3&fmt-out=text/xml
    private String logoutString() {
        StringBuffer buffer = new
StringBuffer(url);
buffer.append(":").append(port).append("/logout.wcap?
35 ");
```

```
        buffer.append("id=").append(userSessionId);
        buffer.append("&fmt-out=text/xml");
        return buffer.toString();
    }

5    //http://wleey006:81/fetchcomponents_by_range.wcap?id
    =t9u9s6he2r5pu9b&dtstart=19990331T112233&dtend=200103
    31T112233&fmt-out=text/xml&maxResults=0

    //retrieve components from calendar
10
        private String retrieveSummaryString(String id,
        int year, int month, int day){
            String start = getFormattedTime(year, month,
        day, 0, 0, 0);
15
            String end = getFormattedTime(year, month,
        day, 23, 59, 59);
            StringBuffer buffer = new
        StringBuffer(url);
20
        buffer.append(":").append(port).append("/fetchcompone
        nts_by_range.wcap?");

            buffer.append("id=").append(id);
25
            buffer.append("&dtstart=").append(start).ap
        pend("&dtend=").append(end);
            buffer.append("&fmt-out=text/xml&maxResults=0");

30
            return buffer.toString();
        }

    /*
        http://myserver:81/
        storecomponents.wcap?id=3423423asdfasf&calid=John1&dt
35    start=19990101T103
```

```
000&dtend=19990101T113000&uid=001&summary=new_year_ev  
ent
```

```
5  */
```

```
/* private String storeComponentString(String url,  
String port, String sessionId, String user, String  
password,
```

```
10         String year, String month, String  
day, String eventId, String summary){
```

```
        String start = getFormattedTime(year, month,  
day, 0, 0, 0);
```

```
15        String end = getFormattedTime(year, month,  
day, 23, 59, 59);
```

```
        StringBuffer buffer = new  
StringBuffer(url);
```

```
20    buffer.append(":").append(port).append("/storecompone  
nts.wcap?id=").append(sessionId);
```

```
        buffer.append("&dtstart=").append(start).ap  
pend("&dtend=").append(end);
```

```
        buffer.append("&uid=").append(eventId).appe  
25 nd("&summary=").append(summary);
```

```
        return buffer.toString();
```

```
    }
```

```
30  */
```

```
/*
```

```
35    http://myserver:81/storeevents.wcap?id='bu9p3eb8x5p2n  
m0q3'&calid=newcal
```

```
&uid=all_params&dtstart=19990811T093000Z&dtend=19990811T163000Z
```

5

```
&summary=all%20params-of-storeevents%20are%20included
```

&location=Mountain-View&icsClass=confidential

10

```
&icsUrl= http://www.mycompany.com
```

```
&duration=PT7H&desc=read%20the%20summary&status=0&isA  
llDay=1
```

15

&geo=37.39;-

```
122.05&rrules="count%3D4%3Bfreq%3Ddaily";"count%3D4%3Bfreq%3Dweekly"
```

20

```
&extrules="count%3D1%3Bfreq%3Dweekly%3Binterval%3D2%3B
byday%3DTU%2CTH"
```

25

```
&rdates=19991015T093000&exdates=19990813T093000&prior
ity=10
```

```
&relatedTo=<777>&resources=board;projector&categories=MEETING
```

30

&contacts=Jane\,John&&alarmStart=19990811T092500Z

```
&alarmEmail=lucys@mycompany.com&orgEmail=jane@mycompany.com;
```

35



```
    */

    /* private String storeEventString(
    //////////////////////////////////////) {
5
        String start = getFormattedTime(year, month,
        day, 0, 0, 0);

        String end = getFormattedTime(year, month,
10    day, 23, 59, 59);
        return buffer.toString();
    }
    */

15

    /**
    * urlConnection to Calendar server with
20    given URL, callType

    * @param String url for the server

    * @param String call type
25

    */
    private String urlConnection(String strUrl,
    String call){
        String retStr = null;
30        try{
            URL url = new URL(strUrl);
            //"http://wleey006.ca.nortel.com:81/login.wcap?user=w
            bin&password=new2day&refresh=1&fmt-out=text/xml");
            InputStream in = url.openStream();
35            BufferedReader bufReader
```

```
                                = new BufferedReader(new
InputStreamReader(in));

//                                DataInputStream data_in = new
5  DataInputStream(in);

                                java.util.Vector contents = new
java.util.Vector();

10                                StringBuffer xmlString = new
StringBuffer();

                                PrintWriter output = null;
                                String sessionLine = "";

15                                String loginLine = "";
                                String logoutLine = "";
                                StringWriter strout = new
StringWriter();

20                                if (call.equals("Login")){
                                    //output = new PrintWriter(new
BufferedWriter(new FileWriter("login.xml")));
                                    output = new PrintWriter(strout);

25                                }

                                if (call.equals("Summary")){
                                    //output = new PrintWriter(new
BufferedWriter(new FileWriter("Summary.xml")));
30                                output = new PrintWriter(strout);

                                //log("PrintWriter is created for
Summary.xml\n");

35
```

```
    }

    else {

5         if(call.equals("Event")){

                //output = new
                PrintWriter(new BufferedWriter(new
                FileWriter("Event.xml")));

10         output = new
                PrintWriter(strout);

                //log("PrintWriter is
                created for Event.xml\n");

15         }
    }

    String line ;

        boolean bflag = false;

20     while((line = bufReader.readLine()) !=
        null){

                // Too dirty, too
                much if.

                log(line);

25         contents.addElement(line);
                if (call.equals("Login")){
                        output.println(line);

                if(line.startsWith("<X-NSCP-WCAP-SESSION-ID>"))

30         sessionLine = line; //
                found the line that contains sesssionID

                        else
                if(line.startsWith("<X-NSCP-WCAP-ERRNO>"))

35         loginLine = line;
```

```

                                else if
      (line.indexOf("<X-NSCP-WCAP-CALENDAR-ID>") >= 0)

                                { // get
5      calendar ID

                                int

      first = line.indexOf(">") + 1;

                                int

      last = line.lastIndexOf("<");
10     calendarId = line.substring(first, last);
      log("Calendar id =" + calendarId);

                                }

      }

      else if( call.equals("Event"))
15

                                {

                                if

      (line.indexOf("<START") >= 0)

                                {

20

      bhasEvent = true;
      log("processing <START>.....</START>");
      StringBuffer humanTime = new StringBuffer();

                                int

25     last = line.indexOf("</START>");
      String theTime = line.substring(7, last -1);
      log("TimeString = " + theTime);
      theTime = ToHumanTime(theTime);
      humanTime.append("<APPDATE>");
30     humanTime.append(curDate);
      humanTime.append("</APPDATE>");

                                line

      = humanTime.toString();
      output.println(line);
35     humanTime = new StringBuffer();

```

000001 24000000

humanTime.append("<APPTIME>");  
humanTime.append(theTime);  
humanTime.append("</APPTIME>");  
5  
line  
= humanTime.toString();  
output.println(line);  
}  
else if  
10 (line.indexOf("<END>") >= 0)  
{  
bhasEvent = true;  
log("processing <END>.....</END>");  
15  
StringBuffer humanTime = new StringBuffer();  
int  
last = line.indexOf("</END>");  
String theTime = line.substring(5, last - 1);  
20 log("TimeString = " + theTime);  
theTime = ToHumanTime(theTime);  
humanTime.append("<APPENDDATE>");  
humanTime.append(curDate);  
humanTime.append("</APPENDDATE>");  
25  
line  
= humanTime.toString();  
output.println(line);  
30  
humanTime = new StringBuffer();  
humanTime.append("<APPENDTIME>");  
humanTime.append(theTime);  
humanTime.append("</APPENDTIME>");  
35  
line

```

= humanTime.toString();
output.println(line);

else
output.println(line);
5
    }
    else if( call.equals("Summary"))
    {
        if
        (line.indexOf("<EVENT") >= 0)
10
            bflag
            = true;
            if
            (line.indexOf("</EVENT") >= 0)
            bflag
15
            = false;
            if (bflag &&
            line.indexOf("<START") >= 0)
            {
20
                bhasEvent = true;
                log("processing <START>.....</START>");
                StringBuffer humanTime = new StringBuffer();

                int
25
                last = line.indexOf("</START>");

                String theTime = line.substring(7, last -1);

                log("TimeString = " + theTime);
30
                theTime = ToHumanTime(theTime);
                humanTime.append("<APPDATE>");
                humanTime.append(curDate);
                humanTime.append("</APPDATE>");
35
                line

```

```

    = humanTime.toString();

    output.println(line);
    humanTime = new StringBuffer();
5   humanTime.append("<APPTIME>");
    humanTime.append(theTime);
    humanTime.append("</APPTIME>");

                                                                    line
10   = humanTime.toString();
    output.println(line);

                                                                    }
                                                                    else
        output.println(line);

15   }

                                                                    else if(
call.equals("Logout")){
    if(line.startsWith("<X-NSCP-WCAP-ERRNO>"))
20   logoutLine
= line;

                                                                    }

}

25   retStr = strout.toString();

    output.close();

30   if ( call.equals("Login")){

                                                                    loginLine =
getValue(loginLine, "<X-NSCP-WCAP-ERRNO>");

35   //

```

```

        if(loginLine.equals("0"))

                                loginSucceed =
loginLine.equals("0")? true: false;
5                                     if( loginSucceed)


                                userSessionId =
getValue(sessionLine, "<X-NSCP-WCAP-SESSION-ID>" );
10                                         //log("User Session
ID = " + userSessionId + " And loginSucceed=" +
loginSucceed);

                                    }

15                                     /*

if( call.equals("Logout")){

20                                     log("Logout is
executed");

                                logoutLine =
getValue(logoutLine, "<X-NSCP-WCAP-ERRNO>"); log("The
logout line is : " + logoutLine);
25                                     logoutSucceed =
logoutLine.equals("-1")? true: false;
}
*/

    bufReader.close();
30         // log(retStr);
            return retStr;
        }catch(Exception ex){
        }

            return null;
35     }

```



```
/**
 * getValue to get session ID from input line
5  * @param String line containning session ID
 * @return String session ID
 */
10
    public String getValue(String selectedLine,
String tag){

    String idString = null;
15
    try {

        //X-NSCP-WCAP-SESSION-ID>

20        //X-NSCP-WCAP-ERRNO

        //String temp =
        "<X-NSCP-WCAP-SESSION-ID>";

25        idString =
selectedLine.substring(tag.length()); // get
substring after <>

        idString = idString.substring(0,
30 idString.indexOf('<'));
    }

    catch ( Exception e ) {

35        e.printStackTrace();
    }
}
```

```
    }  
    return idString.trim();  
  
    }  
5    private String getFormattedTime(int year, int  
    month, int day, int hour, int minute, int second){  
  
        StringBuffer dateTime = new  
StringBuffer(""+year);  
10        if (month< 10){  
            dateTime.append("0");  
        }  
        dateTime.append(month);  
        if (day<10){  
15            dateTime.append("0");  
        }  
        dateTime.append(day).append("T");  
20  
        if ( hour< 10){  
            dateTime.append("0");//  
25        }  
            dateTime.append(hour);  
        if ( minute<10){  
            dateTime.append("0"); //  
        }  
30        dateTime.append(minute);  
        if ( second<10)  
            dateTime.append("0");//  
            dateTime.append(second);  
        log("The time is =:"+dateTime.toString());  
35        return dateTime.toString();
```

```
    }  
    /**  
     * login (String, String, String, String) in  
the calendar with  
5     * @param String url of Calendar server  
  
     * @param String port of the Calendar server  
  
     * @param String username  
10     * @param String password  
  
     * @return boolean true login succeed, false  
means you are not lucky.  
15     */  
  
    private boolean login(String url, String  
port, String user, String password){  
20  
        this.url = url;  
  
        this.port = port;  
  
25        String strLogin = loginString(url,  
port, user, password);  
        log(strLogin);  
        // login  
  
30        try{  
            urlConnection(strLogin, "Login");  
            log("User session ID = " +  
userSessionId);  
            return loginSucceed;  
35        }catch(Exception ex){
```

```
        ex.printStackTrace();
        return false;
    }finally{
        // what should be put here.?
5    }

    /**
     * Convert Calendar Date in Start and End
     elements into speakable date
10    * @param String dateStr ---
    20000909T17000000 to September 9, 2000
     */
    private String ToHumanDate(String theDate)
    {
15        StringBuffer dateBuf = new
        StringBuffer();

        Integer year, month, day;
        year = new Integer(
20    theDate.substring(0, 4));

        month = new Integer(
        theDate.substring(4, 6));

25        day = new Integer(
        theDate.substring(6, 8));

        log("ToHumanDate dateStr: " +
        theDate);
30    dateBuf.append(monthStr[month.intValue() - 1]);

        dateBuf.append("
        ").append(day).append(", ").append(year);
35
```

```

        log("Converted Date: " +
dateBuf.toString());

        return dateBuf.toString();
    }
    /**
     * Convert the time in the START element into
10 speakable time
     * Such as 20000911T150000Z to 8 AM On
Spetember 11, 2000
     */
15 private String ToHumanTime(String theDate)
{
20   log("ToHumanTime&&&&&&&&&&&&&&&&&&&&&&&&&");

       log("theDate =" + theDate);

       Calendar localTime =
25   Calendar.getInstance(TimeZone.getDefault());

       int GMToffset =
localTime.get(Calendar.ZONE_OFFSET) / 3600000;

30   System.out.print("GMT offset = ");

       Integer year1, month1, day1, hour1,
minutel, second1;

35   int year, month, day, hour, minute,
```

5

10

15

20

25

```
hour = hour1.intValue() - 12 - GMToffset;
```

30

```
day = day1.intValue();
```

```
hour = hour1.intValue() - 12 -
```

```
minute = minutel.intValue();
```

```
second = second1.intValue();
```

```
if (hour < 0)
```

1

```
hour += 24;
```

5                    day --;

                  if (day < 0)

                  {

                    month --;

                    if (month < 0)

                      year --;

                  }

10                    }

                  else if (hour > 24)

                    hour -= 12;

                    String timeTag = "AM";

                    Integer dayInt = new Integer(day);

15                      String dayStr = dayInt.toString();

                    Integer yearInt = new Integer(year);

20                      String yearStr = yearInt.toString();

                    if (hour > 12)

                    {

25                          timeTag = "PM";

                        hour -= 12;

30                      }

                    else if (hour == 12)

                        timeTag = " ";

35                      StringBuffer timeStr = new

```
StringBuffer();

        timeStr.append(toString(hour));

5         if (minute > 0)

        timeStr.append(":").append(toString(minute));

        if (second > 0)
10        timeStr.append(":").append(toString(second));

        timeStr.append(" ").append(timeTag);

15        localTime.set(Calendar.YEAR, year);

        localTime.set(Calendar.MONTH, month -
20        1);

        localTime.set(Calendar.DAY_OF_MONTH,
        day);

        Date date = localTime.getTime();

        SimpleDateFormat fd = new
25        SimpleDateFormat("EEEE, MMMMMMMM d, yyyy");

        curDate = fd.format(date);

        //        log("converted time: " +
30        timeStr.toString() + " " + curDate);

        return timeStr.toString();
    }

    private String toString(int value)
    {

35        Integer tmpvalue = new
```



```

Integer(value);
        return new
String(tmpvalue.toString());
5      }

      /**
      logout() of the Calendar
10
      */
      public void logout(){

          String strLogout = logoutString();
15      log(strLogout);

          urlConnection(strLogout, "Logout");

          //return logoutSucceed;
20
      }
      private void log(String s)

      {
25      Log.log(Log.DEBUGGING, getClass(), s);
      }
  }

```

Fig 3 illustrates a full-blown system according to the invention including a session manager 80 and an authentication manager 90. The figure illustrates the different components of the full system as described above. It can be seen that the authentication manager 90 is shown as having multiple servlets within it. This is because each device type has a separate authentication servlet to

accommodate the needs of that specific device type. Similarly, the DMI component 40 has multiple servlets within it -- one servlet for each device type. The broker module 30 is shown as two components - the software MCML script 30A and the finite state machine XML/XSLT engine 30B which executes the script 30A. The AMI component 20 is depicted as two components -- as application EJBs and authentication EJBs. Each group of EJBs has its specific function. The application EJBs provide the data to the broker module while the authentication EJBs provide the authentication data required by the authentication manager. The authentication EJBs also access the applications but only to the extent required by the authentication manager.

Also, as can be seen in Fig 3, the end user devices communicate with an extra layer between itself and the authentication manager. For WAP enabled devices, a WAP gateway 100A receives their data. For a PSTN telephone 50C, the user's voice first goes through a Voice XML engine 100B which converts the user's voice input into data recognizable by the other components. A dispatch servlet 110 sends the signals to their proper servlet in the authentication manager.

For a regular PC 70, its authentication data has to travel through the APM (access policy manager) authorization server 120 and then to the LDAP (lightweight directory access protocol) server 130.

To step through the process, the PSTN telephone, if its user desires access to an application, the sequence of steps are as follows :

1. User dials up Voice Portal DN using a POTS phone

2. Voice Portal static welcome page is invoked, and the server makes a request to the authentication servlet via the initial URL.
3. Authentication servlet does not see a session key embedded in the request URL and therefore issues a challenge page appropriate to the device. It does this by checking the user agent type and other information in the request header, and by then fetching an MCML document that it translates through the appropriate XSL style sheet - which produces a Voice XML form, welcoming the user and asking for authentication (user id and password). The links in this Voice XML document have a temporary authentication key embedded in them by the authentication servlet, to protect this initial transaction.
4. Voice Portal begins to interpret the Voice XML script, which asks for the initial welcome prompt and login request. User listens to welcome prompt and to the request for user id, and keys in or speaks the requested info (we can set this choice either way through Voice XML tags).
5. Voice Portal then interprets the user input and sends a request to the authentication servlet with the posted form data. The authentication servlet checks with APM and authenticates the user. If successful, it generates a session ID that will be appended to all subsequent transaction URLs with our server for this session.

- 5 6. The authentication servlet continues to interpret the PIC MCML flow, which asks it to call the PIC EJB, to get a list of enabled applications from the Personalization Server.
- 10 7. The EJB returns the list, filtered by the EJB adaptor into MCML, which is embedded into the PIC MCML template.
- 15 8. The list has associated hyperlink URLs that are filtered through the session manager, to append a session ID (URL rewriting).
- 20 9. The MCML is translated to Voice XML by the XSLT processor using the VoiceXML style sheet. It is then served to the Voice Portal for interpretation.
- 25 10. The user hears the list (TTS) and selects an application. This causes the Voice Portal to send an HTTP request to the authentication servlet.
- 30 11. The servlet now sees a session ID appended to the URL, and checks its validity. If valid, it passes the request on to the device adaptor servlet (DA), unchallenged.
- 35 12. The DA then retrieves the MCML page for that particular app. (this was encoded in the request URL).
13. It scans for dynamic placeholder tags, and makes calls to the application specific adaptor EJB's (method names and parameters are embedded in MCML) to generate dynamic application content if required.
14. The device adaptor EJB attempts to retrieve a client connection to the app.

from the Session Manager.

15. The session manager cannot find the client, and throws an exception, which is passed on the DA.

5 16. The DA identifies this exception and invokes the authentication EJB associated with this app. which connects using the stored credentials, and then saves a client connection in the Session manager (Single sign-on).

10 17. The device adaptor then re-tries the initial call to the application adaptor, which will now successfully retrieve the client connection from the session manager.

15 18. The EJB connects to the app to get content.

20 19. This content is returned by the EJB's as MCML, through the EJB-DA interface object, which converts the data to MCML. The DA merges this MCML with the static MCML page template.

25 20. The DA then filters all URLs through the Session manager to append session ID. The link to the next MCML page is also generated and appended to the URLs here.

21. The DA then translates the MCML though XSLT to get a Voice XML, which is served back to the client.

30 22. Voice Portal client interprets the returned page, and cycles through the process starting at step 11 above (without the initial authentication exceptions), invoking further MCML pages.

35 23. The cycle continues until the MCML FSM script reaches an exit state, at which

point the DA closes the connection by deleting the session - by making a call to the Session manager. Further requests will then require the authentication cycle to kick-in. User inactivity time-outs can also occur if the user hangs up, or fails to respond within a prescribed delay.

For a WAP enabled cellular telephone or a WAP enabled PDA, the process is as follows :

1. User accesses WAP gateway via Remote Access Server dialup programmed into the WAP handset. User selects a link to access the multi-channel system.
2. As a result, WAP gateway makes a request to the authentication servlet.
3. Authentication servlet does not see a session ID embedded in the request URL and therefore issues a challenge page appropriate to the device. It does this by checking the user agent type in the header, and by then fetching an MCML document that it translates through the appropriate XSL style sheet - which produces a HDML or WML deck, welcoming the user and asking for authentication (user id and password). The links in this document have a temporary authentication key embedded in them by the authentication servlet, to protect this initial transaction. Care must be taken not to exceed the limitations on URL size inherent to some WML and HDML browsers.
4. The handset browser displays the card deck, which asks for the initial welcome prompt and login request. User keys in credentials. These are sent through WAP gateway as a request to the authentication servlet with the posted form data. The authentication servlet checks with APM and authenticates the user. If successful, it generates

a session ID that will be appended to all subsequent transaction URLs with our server for this session.

5. The authentication servlet continues to interpret the PIC MCML flow, which asks it to call the PIC EJB, to get a list of enabled applications from the Personalization Server.
6. The EJB returns a list of application, filtered by the EJB adaptor to produce MCML, which is embedded into the PIC MCML template.
7. The list has associated hyperlink URLs that are filtered through the session manager, to append a session ID (URL rewriting).
8. The MCML is translated to WML or HDML by the XSLT processor using the appropriate style sheet. It is then served to the WAP gateway for forwarding to the handset.
9. The user sees the list and selects an application. This causes the WAP gateway to send a HTTP request to the authentication servlet.
10. The servlet now sees a session ID appended to the URL, and checks its validity. If valid, it passes the request on to the device adaptor servlet (DA), unchallenged.
11. The DA then retrieves the MCML page for that particular app. (this was encoded in the request URL).
12. It scans for dynamic placeholder tags, and makes calls to the application specific adaptor EJB's (method names and parameters are embedded in MCML) to generate dynamic application content if required.
13. The device adaptor EJB attempts to retrieve a client connection to the app. from the Session Manager.

14. The session manager cannot find the client, and throws an exception, which is passed on the DA.
15. The DA identifies this exception and invokes the authentication EJB associated with this app. which connects using the stored credentials, and then saves a client connection in the Session manager (Single sign-on).
16. The device adaptor then re-tries the initial call to the application adaptor, which will now successfully retrieve the client connection from the session manager.
17. The EJB connects to the app to get content.
18. This content is returned by the EJB's as MCML, through the EJB-DA interface object, which converts the data to MCML. The DA merges this MCML with the static MCML page template.
19. The DA then filters all URLs through the Session manager to append session ID. The link to the next MCML page is also generated and appended to the URLs here.
20. The DA then translates the MCML though XSLT to get WML a HDML deck, which is served back to the client.
21. WAP gateway forwards the returned deck to handset, and cycles through the process starting at step 10 (but omitting any initial authentication exceptions) above, invoking further MCML pages.
22. The cycle continues until the MCML FSM script reaches an exit state, at which point the DA closes the connection by deleting the session - by making a call to the Session manager. Further requests will then require the authentication cycle to kick-in. User inactivity time-outs can also occur if the user disconnects, or fails to respond.



within a prescribed delay.

- 5 A person understanding the above-described invention may now conceive of alternative designs, using the principles described herein. All such designs which fall within the scope of the claims appended hereto are considered to be part of the present invention.

00242247 122200